



## Self-inducting air-aspirating foam monitor nozzle (Dispersion jaw)

- Certificate: ISO
- Standard: NFPA 11, UL 162, GB 19156
- Material: Aluminum alloy
- Feature: With pick-up tube, air-aspirating straight jet and fan spray
- W. pressure: 200 psi
- Surface: Hard anodized or red FBE

### Available size

Flow @ 100 psi (7 bar)		Material	Water inlet	Foam concentrate inlet	Proportioning	Ref. No.
GPM	LPM					
505	1920	AL	2-1/2" NH	1-1/4"	0.5% ~ 6%	B7301 (ISO)
758	2880	AL	2-1/2" NH	1-1/4"	0.5% ~ 6%	B7302 (ISO)
1011	3840	AL	3-1/2" NH	1-1/4"	0.5% ~ 6%	B7303 (ISO)
1579	6000	AL	3-1/2" NH	1-1/4"	0.5% ~ 6%	B7304 (ISO)



## Non self-inducting air-aspirating foam monitor nozzle (Dispersion jaw)

- Certificate: ISO
- Standard: NFPA 11, UL 162, GB 19156
- Material: Aluminum alloy
- Feature: Non self-inducting, air-aspirating straight jet and fan spray
- W. pressure: 200 psi
- Surface: Hard anodized or red FBE

### Available size

Flow @ 100 psi (7 bar)		Material	Foam solution inlet	Foam concentrate inlet	Proportioning	Ref. No.
GPM	LPM					
505	1920	AL	2-1/2" NH	/	0.5% ~ 6%	B7401 (ISO)
758	2880	AL	2-1/2" NH	/	0.5% ~ 6%	B7402 (ISO)
1011	3840	AL	3-1/2" NH	/	0.5% ~ 6%	B7403 (ISO)
1579	6000	AL	3-1/2" NH	/	0.5% ~ 6%	B7404 (ISO)