



Remote control (RC) self-inducting air-aspirating nozzle (Dispersion jaw)

- Certificate: ISO
- Standard: NFPA 11, UL 162, GB 19156
- Material: Aluminum alloy
- Feature: Electrical operated, air-aspirating straight jet and fan spray
- Powder: 24VDC
- W. pressure: 200 psi
- Surface: Hard anodized or red FBE

Available size

Flow @ 100 psi (7 bar)		Material	Water inlet	Foam concentrate inlet	Proportioning	Ref. No.
GPM	LPM					
505	1920	AL	2-1/2" NH	1-1/4"	0.5% ~ 6%	B7501 (ISO)
758	2880	AL	2-1/2" NH	1-1/4"	0.5% ~ 6%	B7502 (ISO)
1011	3840	AL	3-1/2" NH	1-1/4"	0.5% ~ 6%	B7503 (ISO)
1263	4800	AL	3-1/2" NH	1-1/4"	0.5% ~ 6%	B7504 (ISO)
1579	6000	AL	3-1/2" NH	1-1/4"	0.5% ~ 6%	B7505 (ISO)



Remote control (RC) non self-inducting air-aspirating nozzle (Dispersion jaw)

- Certificate: ISO
- Standard: NFPA 11, UL 162, GB 19156
- Material: Aluminum alloy
- Feature: Electrical operated, air-aspirating straight jet and fan spray
- Powder: 24VDC
- W. pressure: 200 psi
- Surface: Hard anodized or red FBE

Available size

Flow @ 100 psi (7 bar)		Material	Foam solution inlet	Foam concentrate inlet	Proportioning	Ref. No.
GPM	LPM					
505	1920	AL	2-1/2" NH	/	0.5% ~ 6%	B7601 (ISO)
758	2880	AL	2-1/2" NH	/	0.5% ~ 6%	B7602 (ISO)
1011	3840	AL	3-1/2" NH	/	0.5% ~ 6%	B7603 (ISO)
1263	4800	AL	3-1/2" NH	/	0.5% ~ 6%	B7604 (ISO)
1579	6000	AL	3-1/2" NH	/	0.5% ~ 6%	B7605 (ISO)