



Synthetic fluorine-free foam (SFFF)

- Certificate: UL Listed / FM Approved
- Standard: NFPA 11, UL 162, GB 15308, etc.
- Fire rating: Class B fire of hydrocarbon, also class A fire
- Feature: Low expansion, suitable at solution in fresh water
- Temperature: 1.7°C ~ 49°C in storage and use
- Packing: Jerry can / drum / IBC tote

Available size

Concentrate type	Concentrate % in water	Hazard hydrocarbon	Hazard polar solvent	Pour point	Packing volume (L)	Ref. No.
SFFF	3%	Yes	/	-11.0°C	25 / 200 / 1000	B9501 (UL/FM)



Alcohol-resistant synthetic fluorine-free foam (AR-SFFF)

- Certificate: UL Listed / FM Approved
- Standard: NFPA 11, UL 162, GB 15308, etc.
- Fire rating: Class B fire of hydrocarbon and polar solvent, also as superior wetting agent
- Feature: Low expansion, suitable at solution in fresh water
- Temperature: 1.7°C ~ 49°C in storage and use
- Packing: Jerry can / drum / IBC tote

Available size

Concentrate type	Concentrate % in water	Hazard hydrocarbon	Hazard polar solvent	Pour point	Packing volume (L)	Ref. No.
AR-SFFF	3% x 3%	Yes	Yes	-2.0°C	20 / 200 / 1000	B9601 (UL)
AR-SFFF	3% x 3%	Yes	Yes	-4.0°C	25 / 200 / 1000	B9602 (FM)

Note: For concentrate % in water, it means 3% concentrate at solution for hydrocarbon fire, and 3% concentrate at solution for polar solvent fire.