



shore side

ship side



International shore connection

- Certificate: ISO
- Standard: FSS code
- Material: Brass
- Feature: Connect ship to shore, or ship to ship
- Surface: Rough brass, etc.

Available size

Size	Type	Thread connection	Flanged connection	Working pressure (bar)	Ref. No.
1.5"	Shore side / non-slotted	BSPP (G) / NH / Storz / DSP / Machino / Nakajima	OD 178 mm, FF	10 / 16 / 20	FE2801
1.5"	Ship side / slotted	BSPP (G) / NH / Storz / DSP / Machino / Nakajima	OD 178 mm, FF	10 / 16 / 20	FE2802
2"	Shore side / non-slotted	BSPP (G) / Storz / Machino / Nakajima	OD 178 mm, FF	10 / 16 / 20	FE2803
2"	Ship side / slotted	BSPP (G) / Storz / Machino / Nakajima	OD 178 mm, FF	10 / 16 / 20	FE2804
2.5"	Shore side / non-slotted	BSPP (G) / BS336 / NH / Storz / DSP / Machino / Nakajima	OD 178 mm, FF	10 / 16 / 20	FE2805
2.5"	Ship side / slotted	BSPP (G) / BS336 / NH / Storz / DSP / Machino / Nakajima	OD 178 mm, FF	10 / 16 / 20	FE2806

Note: For each ISC, it includes accessories 1 fiber gasket, 4 brass hexagon bolts M16 x 50 mm, 4 hexagon nuts, and 8 washers.



ISC cabinet

- Certificate: ISO
- Standard: Refer to FSS code
- Feature: Lightweight, corrosive resistance
- Surface: Red polish

Available size

Content	Capacity	Material	Mounting	Dimension W x H x D (mm)	Ref. No.
International shore connection	1.5" / 2" / 2.5", 1 set	Fiberglass	Surface	200 x 200 x 190	FE2811
International shore connection	1.5" / 2" / 2.5", 1 set	Fiberglass	Surface	260 x 240 x 210	FE2812
International shore connection	1.5" / 2" / 2.5", 1 set	Fiberglass	Surface	260 x 240 x 235	FE2813