


Constant gallonage handline fire nozzle (Aluminum)

Constant gallonage handline fire nozzle (Fixed gallonage nozzle) is a simple form of combination nozzle. It maintains a single fixed orifice during pattern adjustment, so to deliver a constant flow from straight stream to wide fog.



- Certificate: ISO
- Standard: UL 401, NFPA 1964
- Fire type: Class A and B (NFPA 10)
- Fire agent: Water, foam solution
- Feature: Fixed flow, straight jet and wide spray
- W. pressure: 200 psi
- Surface: Hard anodized



Main parts and material

Nozzle tip	Aluminum alloy, with rubber bumper	Shutoff	Metal ball valve or slid valve, push-pull bale handle
Pistol grip	Rubber, black, and various other colors	Other components	Spinning or fixed teeth, inlet screen mesh

Available size

Flow @ 100 psi (7 bar)		Material	Inlet	Nozzle type	Shutoff configuration	Ref. No.
GPM	LPM					
60	228	AL	1.5" / 2.5" NH, BS336, etc.	Constant gallonage	Ball valve + pistol grip	Y0201 (ISO)
95	361	AL	1.5" / 2.5" NH, BS336, etc.	Constant gallonage	Ball valve + pistol grip	Y0202 (ISO)
125	475	AL	1.5" / 2.5" NH, BS336, etc.	Constant gallonage	Ball valve + pistol grip	Y0203 (ISO)
150	570	AL	1.5" / 2.5" NH, BS336, etc.	Constant gallonage	Ball valve + pistol grip	Y0204 (ISO)
175	665	AL	1.5" / 2.5" NH, BS336, etc.	Constant gallonage	Ball valve + pistol grip	Y0205 (ISO)
200	760	AL	1.5" / 2.5" NH, BS336, etc.	Constant gallonage	Ball valve + pistol grip	Y0206 (ISO)
150	570	AL	1.5" / 2.5" NH, BS336, etc.	Constant gallonage	Slide valve + pistol grip	Y0207 (ISO)
175	665	AL	1.5" / 2.5" NH, BS336, etc.	Constant gallonage	Slide valve + pistol grip	Y0208 (ISO)

Constant gallonage handline fire nozzle (Aluminum)

Available size

Flow @ 100 psi (7 bar)		Material	Inlet	Nozzle type	Shutoff configuration	Ref. No.
GPM	LPM					
200	760	AL	1.5" / 2.5" NH, BS336, etc.	Constant gallonage	Slide valve + pistol grip	Y0209 (ISO)
250	950	AL	2.5" NH, BS336, etc.	Constant gallonage	Ball valve + pistol grip	Y0210 (ISO)
300	1140	AL	2.5" NH, BS336, etc.	Constant gallonage	Ball valve + pistol grip	Y0211 (ISO)

Note:

1. For configuration, the nozzle also can be supplied only nozzle tip, or with playpipe (For inlet 2.5").
2. For inlet connection, it is available with NH, BS336, Storz, Machino, etc.