


Selectable gallonage handline fire nozzle (Aluminum)

Selectable gallonage handline fire nozzle (Adjustable gallonage nozzle) is a combination nozzle. It allows the operator to manually adjust the dial to change the rated flow. And the flow remains constant from straight stream to wide fog.



- Certificate: FM Approved
- Standard: UL 401, NFPA 1964
- Fire type: Class A and B (NFPA 10)
- Fire agent: Water, foam solution
- Feature: Multiple flow setting on-site, straight jet and wide spray
- W. pressure: 200 psi
- Surface: Hard anodized



Main parts and material

Nozzle tip	Aluminum alloy, with rubber bumper	Shutoff	Metal ball valve, push-pull bale handle
Pistol grip	Rubber, black, and various other colors	Other components	Spinning or fixed teeth, inlet screen mesh

Available size (Source 1 with FM)

Flow @ 100 psi (7 bar)		Material	Inlet	Nozzle type	Shutoff configuration	Ref. No.
GPM	LPM					
30-60-95-125	114-228-361-475	AL	1.5" / 2.5" NH, BS336, etc.	Selectable gallonage	Ball valve + pistol grip	Y0401 (FM)
95-125-150-200	361-475-570-760	AL	1.5" / 2.5" NH, BS336, etc.	Selectable gallonage	Ball valve + pistol grip	Y0402 (FM)
95-125-150-200-250	361-475-570-760-950	AL	2.5" NH, BS336, etc.	Selectable gallonage	Ball valve + pistol grip	Y0403 (FM)

Note:

1. For configuration, the nozzle also can be supplied only nozzle tip, with trigger shutoff, with playpipe (For inlet 2.5").
2. For inlet connection, it is available with NH, BS336, Storz, Machino, etc.

Selectable gallonage handline fire nozzle (Aluminum)

Available size (Source 2 with ISO)

Flow @ 100 psi (7 bar)		Material	Inlet	Nozzle type	Shutoff configuration	Ref. No.
GPM	LPM					
5-10-25-39	19-38-95-150	AL	1.5" / 2" / 2.5" NH, BS336, etc.	Selectable gallonage	Ball valve + pistol grip	Y0421 (ISO)
16-34-62	60-130-235	AL	1.5" / 2" / 2.5" NH, BS336, etc.	Selectable gallonage	Ball valve + pistol grip	Y0422 (ISO)
30-61-95-125	115-230-360-475	AL	1.5" / 2" / 2.5" NH, BS336, etc.	Selectable gallonage	Ball valve + pistol grip	Y0423 (ISO)
95-125-147-200-250	360-475-560-760-950	AL	2" / 2.5" NH, BS336, etc.	Selectable gallonage	Ball valve + pistol grip	Y0424 (ISO)

Note: For inlet connection, it is available with NH, BS336, Storz, Machino, etc.