

Automatic handline fire nozzle

Automatic handline fire nozzle (constant pressure nozzle) has a self-adjusting spring mechanism inside to remains constant pressure through a range of flow. It provides the velocity for an effective stream reach at various flow rates.



· Certificate: ISO


Standard: UL 401, NFPA 1964
Fire type: Class A and B (NFPA 10)
Fire agent: Water, foam solution
Feature: Constant pressure,

straight jet and wide spray

· W. pressure: 200 psi

· Surface: Hard anodized





Main parts and material

Nozzle tip	Aluminum alloy, with rubber bumper	Shutoff	Metal ball valve or slid valve, push-pull bale handle	
Pistol grip	Rubber, black, and various other colors	Other components	Spinning or fixed teeth, inlet screen mesh	

Available size (Source 1)

Flow @ 100 ± 25 psi (7 ± 1.7 bar)		Motorial	Inlet	Nozzle type	Shutoff configuration	Def No
GPM	LPM	Material	iniet	Nozzie type	Siluton configuration	Ref. No.
60 to 200	228 to 760	AL	1.5" / 2.5" NH, BS336, etc.	Automatic	Ball valve + pistol grip	Y0501 (ISO)
75 to 325	285 to 1235	AL	2.5" NH, BS336, etc.	Automatic	Ball valve + pistol grip	Y0502 (ISO)
10 to 125	38 to 475	AL	1.5" / 2.5" NH, BS336, etc.	Automatic	Slide valve + pistol grip	Y0503 (ISO)
70 to 200	266 to 760	AL	1.5" / 2.5" NH, BS336, etc.	Automatic	Slide valve + pistol grip	Y0504 (ISO)
50 to 350	190 to 1330	AL	2.5" NH, BS336, etc.	Automatic	Slide valve + pistol grip	Y0505 (ISO)

Note:

- 1. For configuration, the nozzle also can be supplied only nozzle tip, with trigger shutoff, with playpipe (For inlet 2.5").
- 2. For inlet connection, it is available with NH, BS336, Storz, Machino, etc.

















Automatic handline fire nozzle

Available size (Source 2)

Flow @ 100 ± 25 psi (7 ± 1.7 bar)		Matarial	lulat	Nozzle type	Shutoff configuration	Ref. No.
GPM	LPM	Material	Inlet	NOZZIE type	Siluton configuration	Kei. No.
11 to 105	40 to 400	AL	1.5" / 2" / 2.5" NH, BS336, etc.	Automatic	Slide valve + pistol grip	Y0521 (ISO)
68 to 200	260 to 760	AL	1.5" / 2" / 2.5" NH, BS336, etc.	Automatic	Slide valve + pistol grip	Y0522 (ISO)
105 to 316	400 to 1200	AL	2" / 2.5" NH, BS336, etc.	Automatic	Slide valve + pistol grip	Y0523 (ISO)

Note: For inlet connection, it is available with NH, BS336, Storz, Machino, etc.









