


Multi-purpose handline fire nozzle

Multi-purpose handline fire nozzle is capable to deliver both straight stream and wide fog at the same time or independently. Straight stream provides excellent reach and penetration, whilst fog stream offers rapid cooling and protection.



- Certificate: ISO
- Standard: UL 401, NFPA 1964
- Fire type: Class A and B (NFPA 10)
- Fire agent: Water, foam solution
- Feature: Synchronised straight jet and wide spray
- W. pressure: 200 psi
- Surface: Hard anodized



Main parts and material

Nozzle tip	Aluminum alloy, with rubber bumper	Shutoff	Metal ball valve or slid valve, push-pull bale handle
Pistol grip	Rubber, black, and various other colors	Other components	Spinning or fixed teeth, inlet screen mesh

Available size (Source 1)

Stream + fog @ 100 psi (7 bar)		Material	Inlet	Nozzle type	Shutoff configuration	Ref. No.
GPM	LPM					
36 + 60	137 + 228	AL	1.5" / 2.5" NH, BS336, etc.	Multi-purpose	Ball valve + pistol grip	Y0601 (ISO)
66 + 60	251 + 228	AL	1.5" / 2.5" NH, BS336, etc.	Multi-purpose	Ball valve + pistol grip	Y0602 (ISO)
100 + 60	380 + 228	AL	1.5" / 2.5" NH, BS336, etc.	Multi-purpose	Ball valve + pistol grip	Y0603 (ISO)
160 + 135	608 + 513	AL	1.5" / 2.5" NH, BS336, etc.	Multi-purpose	Ball valve + pistol grip	Y0604 (ISO)
220 + 135	836 + 513	AL	1.5" / 2.5" NH, BS336, etc.	Multi-purpose	Ball valve + pistol grip	Y0605 (ISO)
250 + 135	950 + 513	AL	1.5" / 2.5" NH, BS336, etc.	Multi-purpose	Ball valve + pistol grip	Y0606 (ISO)
160 + 115	608 + 437	AL	1.5" / 2.5" NH, BS336, etc.	Multi-purpose	Slide valve + pistol grip	Y0607 (ISO)

Y06 /

Multi-purpose handline fire nozzle

Available size (Source 1)

Stream + fog @ 100 psi (7 bar)		Material	Inlet	Nozzle type	Shutoff configuration	Ref. No.
GPM	LPM					
220 + 115	836 + 437	AL	1.5" / 2.5" NH, BS336, etc.	Multi-purpose	Slide valve + pistol grip	Y0608 (ISO)
250 + 115	950 + 437	AL	1.5" / 2.5" NH, BS336, etc.	Multi-purpose	Slide valve + pistol grip	Y0609 (ISO)

Note:

1. The nozzle also works efficiently at low operating pressure 50 psi so to reduce firefighter fatigue.
2. For inlet connection, it is available with NH, BS336, Storz, Machino, etc.

Available size (Source 2)

Stream + fog @ 100 psi (7 bar)		Material	Inlet	Nozzle type	Shutoff configuration	Ref. No.
GPM	LPM					
132 + 79	500 + 300	AL	1.5" / 2" / 2.5" NH, BS336, etc.	Multi-purpose	Ball valve + pistol grip	Y0621 (ISO)

Note: For inlet connection, it is available with NH, BS336, Storz, Machino, etc.

Y06 /