



Dual-Agent handline fire nozzle

- Certificate: ISO
- Standard: UL 401, NFPA 1964
- Material: Aluminum alloy
- Feature: Discharge dry chemical at the same time
- W. pressure: 200 psi
- Surface: Hard anodized

Available size

Flow @ 100 psi (7 bar)		Dry chemical agent discharge	Material	Water / foam solution inlet	Dry chemical inlet	Ref. No.
GPM	LPM					
60	228	5 lbs / sec	AL	1" NH	1" NPT	Y1501 (ISO)
95	361	5 lbs / sec	AL	1.5" / 2.5" NH, BS336, etc.	1" NPT	Y1502 (ISO)

Note: For water or foam solution inlet connection, it is available with NH, BS336, Storz, Machino, etc.



Dry chemical handline fire nozzle

- Certificate: ISO
- Standard: UL 401, NFPA 1964
- Material: Aluminum alloy
- Feature: Discharge dry chemical agent
- W. pressure: 200 psi
- Surface: Hard anodized

Available size

Flow @ 100 psi (7 bar)		Dry chemical agent discharge	Material	Dry chemical inlet	Shutoff configuration	Ref. No.
GPM	LPM					
/	/	5 lbs / sec	AL	1" / 1.5" NH, BS336, etc.	Slide valve + pistol grip	Y1601 (ISO)
/	/	2 kg / sec	AL	1.5" / 2" / 2.5" NH, BS336, etc.	Slide valve + pistol grip	Y1602 (ISO)

Note: For inlet connection, it is available with NH, BS336, Storz, Machino, etc.