

Manual operated wheel control fire monitor (Double waterway)

Manual operated wheel control fire monitor (Double waterway) is designed with large clear waterway to deliver a powerful and far-reaching water stream. It is mounted in fixed installation or on vehicle for one man operation.



- Certificate: ISO
- Standard: NFPA 1964, GB 19156
- Connection: Flanged as ANSI Class 150, EN 1092 PN16, etc.
- Feature: Double handwheel control, double waterway, straight jet, wide spray
- Rotation: 360° horizontal
- Elevation: 90° above + 45° below
- W. pressure: 200 psi
- Surface: Hard anodized or red FBE



Main parts and material

Construction	Aluminum alloy	Pre-assembly nozzle	Aluminum alloy
Control	Double handwheel with worm gear	Other components	Double-row SS ball bearing in swivel joint, pressure gauge

Available size

Flow @ 100 psi (7 bar)		Material	Base inlet	Outlet for nozzle	Nozzle type	Ref. No.
GPM	LPM					
316	1200	AL	3" or 4" FLG	2-1/2" NH	Constant gallonage	Y4121 (ISO)
474	1800	AL	3" or 4" FLG	2-1/2" NH	Constant gallonage	Y4122 (ISO)
632	2400	AL	3" or 4" FLG	2-1/2" NH	Constant gallonage	Y4123 (ISO)
316, 474, 632	1200, 1800, 2400	AL	3" or 4" FLG	2-1/2" NH	Adjustable flow	Y4124 (ISO)
474-632-789	1800-2400-3000	AL	3" or 4" FLG	2-1/2" NH	Selectable gallonage	Y4125 (ISO)
Up to 789	Up to 3000	AL	3" or 4" FLG	2-1/2" NH	Smooth bore tip	Y4126 (ISO)