


Dual-purpose electrical remote control portable ground fire monitor

Dual-purpose electrical remote control portable ground fire monitor is suitable for use as a portable monitor or a deck gun so to meet the changing demand of the fire service. It facilitates the effective use of personnel.



- Certificate: ISO
- Standard: NFPA 1964, GB 19156
- Connection: Threaded
- Feature: Portable fire monitor and deck gun
- Rotation: 360° horizontal
- Elevation: From 15° to 85°
- W. pressure: 200 psi
- Surface: Red FBE coating



Main parts and material

Construction	Aluminum alloy, control unit, folding legs, lock pin for easy break apart	Pre-assembly nozzle	Aluminum alloy, electrical remote control
Control	Electrical remote control mechanism, distance up to 200 m	Power	24 VDC, optional 110 or 220 VAC

Available size

Flow @ 100 psi (7 bar)		Material	Base inlet	Outlet for nozzle	Nozzle type	Ref. No.
GPM	LPM					
500	1900	AL	(2) 2-1/2" THD	2-1/2" NH	Constant gallonage	Y5901 (ISO)
750	2850	AL	(2) 2-1/2" THD	2-1/2" NH	Constant gallonage	Y5902 (ISO)
300, 500, 700	1140, 1900, 2660	AL	(2) 2-1/2" THD	2-1/2" NH	Adjustable flow	Y5903 (ISO)
250-400-550-750	950-1520-2090-2850	AL	(2) 2-1/2" THD	2-1/2" NH	Selectable gallonage	Y5904 (ISO)
250, 400, 550, 750	950, 1520, 2090, 2850	AL	(2) 2-1/2" THD	2-1/2" NH	RC adjustable flow	Y5905 (ISO)