



## Constant gallonage fire monitor nozzle (Aluminum)

- Certificate: ISO
- Standard: NFPA 1964, GB 19156
- Material: Aluminum alloy
- Feature: Fixed flow, straight jet and wide spray
- W. pressure: 200 psi
- Surface: Hard anodized or red FBE



### Available size (Source 1)

Flow @ 100 psi (7 bar)		Material	Inlet	Nozzle type	Ref. No.
GPM	LPM				
500	1900	AL	2-1/2" NH	Constant gallonage	Y7201 (ISO)
750	2850	AL	2-1/2" NH	Constant gallonage	Y7202 (ISO)
1000	3800	AL	2-1/2" NH	Constant gallonage	Y7203 (ISO)
1250	4750	AL	2-1/2" NH	Constant gallonage	Y7204 (ISO)

### Available size (Source 2)

Flow @ 100 psi (7 bar)		Material	Inlet	Nozzle type	Ref. No.
GPM	LPM				
316	1200	AL	2-1/2" NH	Constant gallonage	Y7221 (ISO)
474	1800	AL	2-1/2" NH	Constant gallonage	Y7222 (ISO)
632	2400	AL	2-1/2" NH	Constant gallonage	Y7223 (ISO)
789	3000	AL	3-1/2" NH	Constant gallonage	Y7224 (ISO)
947	3600	AL	3-1/2" NH	Constant gallonage	Y7225 (ISO)
1263	4800	AL	3-1/2" NH	Constant gallonage	Y7226 (ISO)
1579	6000	AL	3-1/2" NH	Constant gallonage	Y7227 (ISO)