



Testing playpipe with tip

- Certificate: UL Listed / FM Approved
- Standard: UL 385 / FM 1411
- Feature: Swivel handle and tip, red marlin wound tube
- Operating pres.: 100 psi
- Surface: Rough brass and red paint

Available size

Size	Material	Inlet	With tip	Discharge orifice	Overall length	Ref. No.
2-1/2"	Brass	2-1/2" NH, F	Yes	1-1/8"	30"	F5701
2-1/2"	Brass	2-1/2" NH, F	Yes	1-1/4"	30"	F5702
2-1/2"	Brass	2-1/2" NH, F	Yes	1-1/2"	30"	F5703
2-1/2"	Brass	2-1/2" NH, F	Yes	1-3/4"	30"	F5704
2-1/2"	Brass	2-1/2" NH, F	Non	/	/	F5705



Plain hose nozzle

- Certificate: ISO
- Standard: Refer to NFPA 14, NFPA 1964
- Fire type: Class A and B
- Feature: Straight stream only (no shut-off)
- Operating pres.: 100 psi
- Surface: Rough / polished / red plastic

Available size

Size	Material	Inlet	With tip	Discharge orifice	Overall length	Ref. No.
1-1/2"	Polycarbonate	1-1/2" NH, F	Non	1/2"	10"	F5711
1-1/2"	Brass	1-1/2" NH, F	Non	1/2"	10"	F5712
2-1/2"	Brass	2-1/2" NH, F	Non	1"	12"	F5713
1-1/2"	Brass	1-1/2" NH, F	Yes	9 mm	360 mm	F5714
2-1/2"	Brass	2-1/2" NH, F	Yes	16 mm	460 mm	F5715