


Manual operated single wheel control fire monitor

Manual operated single wheel control fire monitor is designed with large clear waterway to deliver a powerful and far-reaching water stream. It is mounted in fixed installation or on vehicle for one man operation.



- Certificate: FM Approved
- Standard: NFPA 1964, GB 19156
- Connection: Threaded, flanged as ANSI Class 150, EN 1092 PN16, etc.
- Feature: Single handwheel control, straight jet, wide spray
- Rotation: 360° horizontal
- Elevation: 70° above + 60° below
- W. pressure: 200 psi
- Surface: Red FBE coating



Main parts and material

Construction	Brass	Pre-assembly nozzle	Brass
Control	Single handwheel with worm gear	Other components	Double-row SS ball bearing in swivel joint, twist lock

Available size

Flow @ 100 psi (7 bar)		Material	Base inlet	Outlet for nozzle	Nozzle type	Ref. No.
GPM	LPM					
500	1900	Brass	3" THD / 3" or 4" FLG	2-1/2" NH	Constant gallonage	Y4201 (FM)
750	2850	Brass	3" THD / 3" or 4" FLG	2-1/2" NH	Constant gallonage	Y4202 (FM)
1000	3800	Brass	3" THD / 3" or 4" FLG	2-1/2" NH	Constant gallonage	Y4203 (FM)
1250	4750	Brass	3" THD / 3" or 4" FLG	2-1/2" NH	Constant gallonage	Y4204 (FM)
300, 500, 800, 1000	1140, 1900, 3040, 3800	Brass	3" THD / 3" or 4" FLG	2-1/2" NH	Adjustable flow	Y4205 (FM)
500-750-1000-1250	1900-2850-3800-4750	Brass	3" THD / 3" or 4" FLG	2-1/2" NH	Selectable gallonage	Y4206 (FM)

Note: For flanged type base inlet, it is FM. For threaded type base inlet, it is ISO.