


# Portable ground fire monitor

Portable ground fire monitor is compact, lightweight for easy to carry but delivers much more water. It is simple to set up for quick attack operation, and can be left unmanned at the fire scene to conserve manpower.



- Certificate: ISO
- Standard: NFPA 1964, GB 19156
- Connection: 2-1/2" NH, Storz, etc.
- Feature: Portable, compact folding leg
- Rotation: 20° each side of center
- Elevation: From 30° to 60° unmanned, etc.
- W. pressure: 200 psi
- Surface: Red FBE coating



## Main parts and material

<b>Construction</b>	Aluminum alloy, with folding legs fitted carbide-tipped spikes	<b>Pre-assembly nozzle</b>	Aluminum alloy
<b>Control</b>	Manual	<b>Other components</b>	Ball shutoff, large lifting handle, anchor safety strap

## Available size (Source 1)

Flow @ 100 psi (7 bar)		Material	Base inlet	Outlet for nozzle	Nozzle type	Ref. No.
GPM	LPM					
150, 250, 350, 500	570, 950, 1330, 1900	AL	2-1/2" THD	2-1/2" NH	Adjustable flow	Y5601 (ISO)
Up to 500	Up to 1900	AL	2-1/2" THD	2-1/2" NH	Smooth bore tip	Y5602 (ISO)
75 to 325	285 to 1235	AL	2-1/2" THD	2-1/2" NH	Handline fire nozzle	Y5603 (ISO)
150, 250, 350, 500	570, 950, 1330, 1900	AL	(2) 2-1/2" THD	2-1/2" NH	Adjustable flow	Y5604 (ISO)
Up to 500	Up to 1900	AL	(2) 2-1/2" THD	2-1/2" NH	Smooth bore tip	Y5605 (ISO)
75 to 325	285 to 1235	AL	(2) 2-1/2" THD	2-1/2" NH	Handline fire nozzle	Y5606 (ISO)

# Portable ground fire monitor

## Available size (Source 2)

Flow @ 100 psi (7 bar)		Material	Base inlet	Outlet for nozzle	Nozzle type	Ref. No.
GPM	LPM					
316, 474, 632	1200, 1800, 2400	AL	2-1/2" NH, BS336, etc.	2-1/2" NH	Adjustable flow	Y5621 (ISO)
Up to 789	Up to 3000	AL	2-1/2" NH, BS336, etc.	2-1/2" NH	Smooth bore tip	Y5622 (ISO)
316 to 1263	1200 to 4800	AL / SS304	(2) 2-1/2" NH, BS336, etc.	2-1/2" NH	Automatic	Y5623 (ISO)

**Note:** For base inlet, it is available with NH, BS336, Storz, Machino, etc.