


Dual-purpose portable ground fire monitor

Dual-purpose portable ground fire monitor is suitable for use as a portable fire monitor or a deck gun so to meet the changing demand of the fire service. It is compact, lightweight, and simple to set up for quick attack operation.



- Certificate: ISO
- Standard: NFPA 1964, GB 19156
- Connection: Threaded, single or dual
- Feature: Portable monitor and deck gun
- Rotation: 180° horizontal
- Elevation: From 12° to 75°, inbuilt safety stop
- W. pressure: 200 psi
- Surface: Red FBE coating



Main parts and material

Construction	AL, with folding legs fitted carbide-tipped spikes, lock pin for easy break apart	Pre-assembly nozzle	Aluminum alloy
Control	Single handwheel with worm gear	Other components	Pressure gauge, large lifting handle, anchor safety strap, ball shutoff as option

Available size

Flow @ 100 psi (7 bar)		Material	Base inlet	Outlet for nozzle	Nozzle type	Ref. No.
GPM	LPM					
500	1900	AL	2-1/2" to 5" THD	2-1/2" NH	Constant gallonage	Y5801 (ISO)
750	2850	AL	2-1/2" to 5" THD	2-1/2" NH	Constant gallonage	Y5802 (ISO)
300, 500, 700	1140, 1900, 2660	AL	2-1/2" to 5" THD	2-1/2" NH	Adjustable flow	Y5803 (ISO)
250-400-550-750	950-1520-2090-2850	AL	2-1/2" to 5" THD	2-1/2" NH	Selectable gallonage	Y5804 (ISO)
500	1900	AL	(2) 2-1/2" THD	2-1/2" NH	Constant gallonage	Y5805 (ISO)
750	2850	AL	(2) 2-1/2" THD	2-1/2" NH	Constant gallonage	Y5806 (ISO)
300, 500, 700	1140, 1900, 2660	AL	(2) 2-1/2" THD	2-1/2" NH	Adjustable flow	Y5807 (ISO)
250-400-550-750	950-1520-2090-2850	AL	(2) 2-1/2" THD	2-1/2" NH	Selectable gallonage	Y5808 (ISO)

Note:

1. For base inlet 2-1/2" to 5" THD, it is available with size 2-1/2", 3", 3-1/2", 4", and 5".
2. For base inlet (2) 2-1/2" THD, it is also available with dual integrated ball shutoff.

Y58 /