



Adjustable flow fire monitor nozzle (Brass)

- Certificate: FM Approved
- Standard: NFPA 1964, GB 19156
- Material: Brass
- Feature: Shut down to change flow setting, straight jet and wide spray
- W. pressure: 200 psi
- Surface: Rough

Available size

Flow @ 100 psi (7 bar)		Material	Inlet	Nozzle type	Ref. No.
GPM	LPM				
150, 250, 350, 500	570, 950, 1330, 1900	Brass	2-1/2" NH	Adjustable flow	Y7301 (ISO)
300, 500, 700	1140, 1900, 2660	Brass	2-1/2" NH	Adjustable flow	Y7302 (FM)
300, 500, 800, 1000	1140, 1900, 3040, 3800	Brass	2-1/2" NH	Adjustable flow	Y7303 (FM)



Adjustable flow fire monitor nozzle (Aluminum)

- Certificate: ISO
- Standard: NFPA 1964, GB 19156
- Material: Aluminum alloy
- Feature: Shut down to change flow setting, straight jet and wide spray
- W. pressure: 200 psi
- Surface: Hard anodized or red FBE

Available size

Flow @ 100 psi (7 bar)		Material	Inlet	Nozzle type	Ref. No.
GPM	LPM				
150, 250, 350, 500	570, 950, 1330, 1900	AL	2-1/2" NH	Adjustable flow	Y7401 (ISO)
300, 500, 700	1140, 1900, 2660	AL	2-1/2" NH	Adjustable flow	Y7402 (ISO)
300, 500, 800, 1000	1140, 1900, 3040, 3800	AL	2-1/2" NH	Adjustable flow	Y7403 (ISO)
316, 474, 632	1200, 1800, 2400	AL	2-1/2" NH	Adjustable flow	Y7404 (ISO)