



## Selectable gallonage fire monitor nozzle (Brass)

- Certificate: FM Approved
- Standard: NFPA 1964, GB 19156
- Material: Brass
- Feature: Multiple flow setting on-site, straight jet and wide spray
- W. pressure: 200 psi
- Surface: Rough

### Available size

Flow @ 100 psi (7 bar)		Material	Inlet	Nozzle type	Ref. No.
GPM	LPM				
250-400-550-750	950-1520-2090-2850	Brass	2-1/2" NH	Selectable gallonage	Y7501 (ISO)
500-750-1000-1250	1900-2850-3800-4750	Brass	2-1/2" NH	Selectable gallonage	Y7502 (FM)



## Selectable gallonage fire monitor nozzle (Aluminum)

- Certificate: ISO
- Standard: NFPA 1964, GB 19156
- Material: Aluminum alloy
- Feature: Multiple flow setting on-site, straight jet and wide spray
- W. pressure: 200 psi
- Surface: Hard anodized or red FBE

### Available size

Flow @ 100 psi (7 bar)		Material	Inlet	Nozzle type	Ref. No.
GPM	LPM				
250-400-550-750	950-1520-2090-2850	AL	2-1/2" NH	Selectable gallonage	Y7601 (ISO)
500-750-1000-1250	1900-2850-3800-4750	AL	2-1/2" NH	Selectable gallonage	Y7602 (ISO)
474-632-789	1800-2400-3000	AL	2-1/2" NH	Selectable gallonage	Y7603 (ISO)