



## Remote control (RC) fire monitor nozzle

- Certificate: ISO
- Standard: NFPA 1964, GB 19156
- Material: Aluminum alloy
- Feature: Electrical operated, straight jet and wide spray
- W. pressure: 200 psi
- Surface: Red FBE coating

### Available size (Source 1)

Flow @ 100 psi (7 bar)		Material	Inlet	Nozzle type	Ref. No.
GPM	LPM				
250, 400, 550, 750	950, 1520, 2090, 2850	AL	2-1/2" NH	RC adjustable flow	Y8101 (ISO)
300 to 1250	1140 to 4750	AL	2-1/2" NH	RC automatic	Y8102 (ISO)
1000	3800	AL	3-1/2" NH	RC constant gallonage	Y8103 (ISO)
1250	4750	AL	3-1/2" NH	RC constant gallonage	Y8104 (ISO)
1500	5700	AL	3-1/2" NH	RC constant gallonage	Y8105 (ISO)

### Available size (Source 2)

Flow @ 100 psi (7 bar)		Material	Inlet	Nozzle type	Ref. No.
GPM	LPM				
316	1200	AL	2-1/2" NH	RC constant gallonage	Y8121 (ISO)
474	1800	AL	2-1/2" NH	RC constant gallonage	Y8122 (ISO)
632	2400	AL	2-1/2" NH	RC constant gallonage	Y8123 (ISO)
316, 474, 632	1200, 1800, 2400	AL	2-1/2" NH	RC adjustable flow	Y8124 (ISO)
316 to 1263	1200 to 4800	AL	2-1/2" NH	RC automatic	Y8125 (ISO)
789	3000	AL	3-1/2" NH	RC constant gallonage	Y8126 (ISO)
947	3600	AL	3-1/2" NH	RC constant gallonage	Y8127 (ISO)
1263	4800	AL	3-1/2" NH	RC constant gallonage	Y8128 (ISO)
1579	6000	AL	3-1/2" NH	RC constant gallonage	Y8129 (ISO)