


# Storz lever operated hand-held branchpipe

Branchpipe connects to water supply via a fire hose and is used to project water for fire service use. For hand-held branchpipe, it is smooth bore, lever operated to control flow pattern to full jet, spray jet or shut.



- Certificate: ISO
- Standard: Refer to EN 15182-3
- Spray angle: 15° ~ 27°
- Throw at 6 bar: 30m at full jet, 15m at spray jet
- Flow at 6 bar: 230LPM at full jet, 220LPM at full cone
- Hydraulic test: 22.5 bar
- Surface: Black or red plastic



## Main parts and material

<b>Body / nozzle</b>	Aluminum alloy, BS 1459 LM25	<b>Body shaft gripping device</b>	Rubber covered aluminum
<b>Inlet</b>	Aluminum alloy, Storz	<b>Open and shut-off device</b>	Aluminum alloy, lever with ball valve control

## Available size

Size	Barrel material	Inlet	Nozzle size (mm)	Normal pressure (bar)	Ref. No.
1.5"	AL, black coating	Storz 38	9	16	FE3601
1.5"	Rubber, red	Storz 38	9	16	FE3602
2"	AL, black coating	Storz C 52	12	16	FE3603
2"	Rubber, red	Storz C 52	12	16	FE3604
2.5"	AL, black coating	Storz 65	16	16	FE3605
2.5"	Rubber, red	Storz 65	16	16	FE3606