


# DSP lever operated hand-held branchpipe

Branchpipe connects to water supply via a fire hose and is used to project water for fire service use. For hand-held branchpipe, it is smooth bore, lever operated to control flow pattern to full jet, spray jet or shut.



- Certificate: ISO
- Standard: Refer to EN 15182-3
- Spray angle: 15° ~ 27°
- Throw at 6 bar: 30m at full jet, 15m at spray jet
- Flow at 6 bar: 230LPM at full jet, 220LPM at full cone
- Hydraulic test: 22.5 bar
- Surface: Black or red plastic



## Main parts and material

<b>Body / nozzle</b>	Aluminum alloy, BS 1459 LM25	<b>Body shaft gripping device</b>	Rubber covered aluminum
<b>Inlet</b>	Aluminum alloy, DSP	<b>Open and shut-off device</b>	Aluminum alloy, lever with ball valve control

## Available size

Size	Barrel material	Inlet	Nozzle size (mm)	Normal pressure (bar)	Ref. No.
1.5"	AL, black coating	DSP 40	12	16	FE3701
1.5"	Rubber, red	DSP 40	12	16	FE3702
2.5"	AL, black coating	DSP 65	16	16	FE3703
2.5"	Rubber, red	DSP 65	16	16	FE3704