

Machino lever operated hand-held branchpipe

Branchpipe connects to water supply via a fire hose and is used to project water for fire service use. For hand-held branchpipe, it is smooth bore, lever operated to control flow pattern to full jet, spray jet or shut.



· Certificate: ISO

· Standard: Refer to EN 15182-3


• Spray angle: $15^{\circ} \sim 27^{\circ}$

· Throw at 6 bar: 30m at full jet, 15m at spray jet

· Flow at 6 bar: 230LPM at full jet, 220LPM at full cone

· Hydraulic test: 22.5 bar

· Surface: Black or red plastic



Main parts and material

Body / nozzle	Aluminum alloy, BS 1459 LM25	alloy, BS 1459 LM25 Body shaft gripping device Rub	
Inlet	Aluminum alloy, machino	Open and shut-off device	Aluminum alloy, lever with ball valve control

Available size

Size	Barrel material	Inlet	Nozzle size (mm)	Norminal pressure (bar)	Ref. No.
1.5"	AL, black coating	Machino 40A	12	16	FE3801
1.5"	Rubber, red	Machino 40A	12	16	FE3802
2"	AL, black coating	Machino 50A	12	16	FE3803
2"	Rubber, red	Machino 50A	12	16	FE3804
2.5"	AL, black coating	Machino 65A	16	16	FE3805
2.5"	Rubber, red	Machino 65A	16	16	FE3806









