

## Piercing applicator fire nozzle



- Certificate: ISO
- Standard: UL 401, NFPA 1964
- Material: Aluminum alloy body + SS tip
- Feature: Hardened tool steel point, wide spray
- W. pressure: 200 psi
- Surface: Hard anodized



### Available size

Flow @ 100 psi (7 bar)		Material	Inlet	Nozzle type	Shutoff configuration	Ref. No.
GPM	LPM					
15	57	AL	1" NH	Piercing applicator, straight	Trigger + pistol grip	Y1101 (ISO)
36	135	AL	1.5" / 2" / 2.5" NH, BS336, etc.	Piercing applicator, straight	Ball valve + pistol grip	Y1102 (ISO)
36	135	AL	1.5" / 2" / 2.5" NH, BS336, etc.	Piercing applicator, curved	Ball valve + pistol grip	Y1103 (ISO)

**Note:** For inlet connection, it is available with NH, BS336, Storz, Machino, etc.



## Water wall fire nozzle

- Certificate: ISO
- Standard: UL 401, NFPA 1964
- Material: Aluminum alloy
- Feature: Wide spray, angle 180°
- W. pressure: 200 psi
- Surface: Hard anodized



### Available size

Flow @ 100 psi (7 bar)		Material	Inlet	Nozzle type	Water wall (W x H, m)	Ref. No.
GPM	LPM					
132	500	AL	2" / 2.5" NH, BS336, etc.	Fan type baffle	24 x 7	Y1201 (ISO)
211	800	AL	2.5" NH, BS336, etc.	Fan type baffle	24 x 7	Y1202 (ISO)
264	1000	AL	2.5" NH, BS336, etc.	Fan type baffle	24 x 7	Y1203 (ISO)

**Note:** For inlet connection, it is available with NH, BS336, Storz, Machino, etc.