

Standard retainer strap



- Certificate: ISO
- Standard: Refer to UL 203
- Material: Carbon steel
- Surface: Pre-galvanized
- Application: Fitted with clamp to reduce movement

Available size

Max flange width	Number of hole	Rod size (RS)		Width	Length	Ref. No.
		UNC	Metric			
4" (102mm)	1	3/8"	M10	15/16" (24mm)	6" (152mm)	P6701
6" (152mm)	1	3/8"	M10	15/16" (24mm)	8" (204mm)	P6702
6" (152mm)	1	1/2"	M12	15/16" (24mm)	8" (204mm)	P6703
8" (204mm)	1	3/8"	M10	15/16" (24mm)	10" (254mm)	P6704
8" (204mm)	1	1/2"	M12	15/16" (24mm)	10" (254mm)	P6705
8" (204mm)	1	5/8"	M16	1-3/16" (30mm)	10" (254mm)	P6706
8" (204mm)	1	3/4"	M20	1-3/16" (30mm)	10" (254mm)	P6707

Two hole retainer strap



- Certificate: ISO
- Standard: Refer to UL 203
- Material: Carbon steel
- Surface: Pre-galvanized
- Application: Fitted with clamp to reduce movement

Available size

Max flange width	Number of hole	Rod size (RS)		Width	Length	Ref. No.
		RS1	RS2			
4" (102mm)	2	3/8" (M10)	1/2" (M12)	15/16" (24mm)	6" (152mm)	P6721
6" (152mm)	2	3/8" (M10)	1/2" (M12)	15/16" (24mm)	8" (204mm)	P6722
8" (204mm)	2	3/8" (M10)	1/2" (M12)	15/16" (24mm)	10" (254mm)	P6723
10" (254mm)	2	3/8" (M10)	1/2" (M12)	15/16" (24mm)	12" (305mm)	P6724
12" (305mm)	2	3/8" (M10)	1/2" (M12)	15/16" (24mm)	14" (356mm)	P6725
14" (356mm)	2	3/8" (M10)	1/2" (M12)	15/16" (24mm)	16" (406mm)	P6726
16" (406mm)	2	3/8" (M10)	1/2" (M12)	15/16" (24mm)	18" (457mm)	P6727