


Manual operated lever control fire monitor

Manual operated lever control fire monitor is designed with large clear waterway to deliver a powerful and far-reaching water stream. It is mounted in fixed installation or on vehicle for one man operation.



- Certificate: FM Approved
- Standard: NFPA 1964, GB 19156
- Connection: Flanged as ANSI Class 150, EN 1092 PN16, etc.
- Feature: Lever control, straight jet, wide spray
- Rotation: 360° horizontal
- Elevation: 90° above + 60° below, etc.
- W. pressure: 200 psi
- Surface: Red FBE coating, etc.



Main parts and material

Construction	Brass, aluminum alloy or SS304	Pre-assembly nozzle	Brass or aluminum alloy
Control	Hand lever or tiller, SS	Other components	Double-row SS ball bearing in swivel joint, twist lock

Available size (Source 1 with FM)

Flow @ 100 psi (7 bar)		Material	Base inlet	Outlet for nozzle	Nozzle type	Ref. No.
GPM	LPM					
500	1900	Brass	3" or 4" FLG	2-1/2" NH	Constant gallonage	Y3301 (FM)
750	2850	Brass	3" or 4" FLG	2-1/2" NH	Constant gallonage	Y3302 (FM)
1000	3800	Brass	3" or 4" FLG	2-1/2" NH	Constant gallonage	Y3303 (FM)
1250	4750	Brass	3" or 4" FLG	2-1/2" NH	Constant gallonage	Y3304 (FM)
300, 500, 800, 1000	1140, 1900, 3040, 3800	Brass	3" or 4" FLG	2-1/2" NH	Adjustable flow	Y3305 (FM)
500-750-1000-1250	1900-2850-3800-4750	Brass	3" or 4" FLG	2-1/2" NH	Selectable gallonage	Y3306 (FM)
1500	5700	Brass	4" or 6" FLG	3-1/2" NH	Constant gallonage	Y3307 (FM)
2000	7600	Brass	4" or 6" FLG	3-1/2" NH	Constant gallonage	Y3308 (FM)
500	1900	AL	3" or 4" FLG	2-1/2" NH	Constant gallonage	Y3309 (ISO)

Manual operated lever control fire monitor

Available size (Source 1 with FM)

Flow @ 100 psi (7 bar)		Material	Base inlet	Outlet for nozzle	Nozzle type	Ref. No.
GPM	LPM					
750	2850	AL	3" or 4" FLG	2-1/2" NH	Constant gallonage	Y3310 (ISO)
1000	3800	AL	3" or 4" FLG	2-1/2" NH	Constant gallonage	Y3311 (ISO)
1250	4750	AL	3" or 4" FLG	2-1/2" NH	Constant gallonage	Y3312 (ISO)
300, 500, 800, 1000	1140, 1900, 3040, 3800	AL	3" or 4" FLG	2-1/2" NH	Adjustable flow	Y3313 (ISO)
500-750-1000-1250	1900-2850-3800-4750	AL	3" or 4" FLG	2-1/2" NH	Selectable gallonage	Y3314 (ISO)
300 to 1000	1140 to 3800	AL	3" or 4" FLG	2-1/2" NH	Automatic	Y3315 (ISO)

Available size (Source 2 with ISO)

Flow @ 100 psi (7 bar)		Material	Base inlet	Outlet for nozzle	Nozzle type	Ref. No.
GPM	LPM					
316	1200	AL	3" or 4" FLG	2-1/2" NH	Constant gallonage	Y3321 (ISO)
474	1800	AL	3" or 4" FLG	2-1/2" NH	Constant gallonage	Y3322 (ISO)
632	2400	AL	3" or 4" FLG	2-1/2" NH	Constant gallonage	Y3323 (ISO)
316, 474, 632	1200, 1800, 2400	AL	3" or 4" FLG	2-1/2" NH	Adjustable flow	Y3324 (ISO)
474-632-789	1800-2400-3000	AL	3" or 4" FLG	2-1/2" NH	Selectable gallonage	Y3325 (ISO)
316 to 1263	1200 to 4800	AL	3" or 4" FLG	2-1/2" NH	Automatic	Y3326 (ISO)
Up to 789	Up to 3000	AL	3" or 4" FLG	2-1/2" NH	Smooth bore tip	Y3327 (ISO)
789	3000	AL	3" or 4" FLG	3-1/2" NH	Constant gallonage	Y3328 (ISO)
947	3600	AL	3" or 4" FLG	3-1/2" NH	Constant gallonage	Y3329 (ISO)
1263	4800	AL	3" or 4" FLG	3-1/2" NH	Constant gallonage	Y3330 (ISO)
1579	6000	AL	3" or 4" FLG	3-1/2" NH	Constant gallonage	Y3331 (ISO)
316, 474, 632	1200, 1800, 2400	SS	3" or 4" FLG	2-1/2" NH	Adjustable flow	Y3332 (ISO)
1263	4800	SS	3" or 4" FLG	3-1/2" NH	Constant gallonage	Y3333 (ISO)

Note: For fire monitor with SS material construction, the pre-assembly nozzle is aluminum. Brass nozzle is also available.