


Portable ground fire monitor

Portable ground fire monitor is compact, lightweight for easy to carry but delivers much more water. It is simple to set up for quick attack operation, and can be left unmanned at the fire scene to conserve manpower.



- Certificate: ISO
- Standard: NFPA 1964, GB 19156
- Connection: 2-1/2" NH, Storz, etc.
- Feature: Portable, compact folding leg
- Rotation: 20° each side of center
- Elevation: From 30° to 60° unmanned, etc.
- W. pressure: 200 psi
- Surface: Red FBE coating



Main parts and material

| | | | |
|---------------------|--|----------------------------|---|
| Construction | Aluminum alloy, with folding legs fitted carbide-tipped spikes | Pre-assembly nozzle | Aluminum alloy |
| Control | Manual | Other components | Ball shutoff, large lifting handle, anchor safety strap |

Available size (Source 1)

| Flow @ 100 psi (7 bar) | | Material | Base inlet | Outlet for nozzle | Nozzle type | Ref. No. |
|------------------------|----------------------|----------|----------------|-------------------|----------------------|-------------|
| GPM | LPM | | | | | |
| 150, 250, 350, 500 | 570, 950, 1330, 1900 | AL | 2-1/2" THD | 2-1/2" NH | Adjustable flow | Y5601 (ISO) |
| Up to 500 | Up to 1900 | AL | 2-1/2" THD | 2-1/2" NH | Smooth bore tip | Y5602 (ISO) |
| 75 to 325 | 285 to 1235 | AL | 2-1/2" THD | 2-1/2" NH | Handline fire nozzle | Y5603 (ISO) |
| 150, 250, 350, 500 | 570, 950, 1330, 1900 | AL | (2) 2-1/2" THD | 2-1/2" NH | Adjustable flow | Y5604 (ISO) |
| Up to 500 | Up to 1900 | AL | (2) 2-1/2" THD | 2-1/2" NH | Smooth bore tip | Y5605 (ISO) |
| 75 to 325 | 285 to 1235 | AL | (2) 2-1/2" THD | 2-1/2" NH | Handline fire nozzle | Y5606 (ISO) |

Portable ground fire monitor

Available size (Source 2)

| Flow @ 100 psi (7 bar) | | Material | Base inlet | Outlet for nozzle | Nozzle type | Ref. No. |
|------------------------|------------------|----------|----------------------------|-------------------|-----------------|-------------|
| GPM | LPM | | | | | |
| 316, 474, 632 | 1200, 1800, 2400 | AL | 2-1/2" NH, BS336, etc. | 2-1/2" NH | Adjustable flow | Y5621 (ISO) |
| Up to 789 | Up to 3000 | AL | 2-1/2" NH, BS336, etc. | 2-1/2" NH | Smooth bore tip | Y5622 (ISO) |
| 316 to 1263 | 1200 to 4800 | AL | (2) 2-1/2" NH, BS336, etc. | 2-1/2" NH | Automatic | Y5623 (ISO) |
| 316 to 1263 | 1200 to 4800 | SS | (2) 2-1/2" NH, BS336, etc. | 2-1/2" NH | Automatic | Y5624 (ISO) |

Note:

1. For base inlet, it is available with NH, BS336, Storz, Machino, etc.
2. For fire monitor with SS material construction, the pre-assembly nozzle is aluminum. Brass nozzle is also available.