



## Threaded outlet oblique type landing valve

- Certificate: ISO
- Standard: DIN 14461-3
- Material: Copper alloy / aluminum
- Feature: Oblique type, BSP outlet
- Surface: Rough / polish / red coating

### Available size

Size	Type	Inlet	Outlet	Working pressure (bar)	Ref. No.
DN 40 (1.5")	Oblique	BSPP (G) 1.5", M or F	BSPP (G) 1.5", M	16	FE1601
DN 50 (2")	Oblique	BSPP (G) 2", M or F	BSPP (G) 2", M	16	FE1602
DN 65 (2.5")	Oblique	BSPP (G) 2.5", M or F	BSPP (G) 2.5", M	16	FE1603
DN 80 (3")	Oblique	BSPP (G) 3", M or F	BSPP (G) 2.5", M	16	FE1604



## Threaded outlet angle type landing valve

- Certificate: ISO
- Standard: DIN 14461-3
- Material: Copper alloy / aluminum
- Feature: Angle type, BSP outlet
- Surface: Rough / polish / red coating

### Available size

Size	Type	Inlet	Outlet	Working pressure (bar)	Ref. No.
DN 40 (1.5")	Angle	BSPP (G) 1.5", M or F	BSPP (G) 1.5", M	16	FE1611
DN 50 (2")	Angle	BSPP (G) 2", M or F	BSPP (G) 2", M	16	FE1612
DN 65 (2.5")	Angle	BSPP (G) 2.5", M or F	BSPP (G) 2.5", M	16	FE1613
DN 80 (3")	Angle	BSPP (G) 3", M or F	BSPP (G) 2.5", M	16	FE1614