



shore side

ship side



International shore connection

- Certificate: ISO
- Standard: FSS code
- Material: Brass
- Feature: Connect ship to shore, or ship to ship
- Surface: Rough brass, etc.

Available size

| Size | Type | Thread connection | Flanged connection | Working pressure (bar) | Ref. No. |
|--------------|--------------------------|--|--------------------|------------------------|----------|
| DN 40 (1.5") | Shore side / non-slotted | BSPP (G) / NH / Storz / DSP / Machino / Nakajima | OD 178 mm, FF | 10 / 16 / 20 | FE2801 |
| DN 40 (1.5") | Ship side / slotted | BSPP (G) / NH / Storz / DSP / Machino / Nakajima | OD 178 mm, FF | 10 / 16 / 20 | FE2802 |
| DN 50 (2") | Shore side / non-slotted | BSPP (G) / Storz / Machino / Nakajima | OD 178 mm, FF | 10 / 16 / 20 | FE2803 |
| DN 50 (2") | Ship side / slotted | BSPP (G) / Storz / Machino / Nakajima | OD 178 mm, FF | 10 / 16 / 20 | FE2804 |
| DN 65 (2.5") | Shore side / non-slotted | BSPP (G) / BS336 / NH / Storz / DSP / Machino / Nakajima | OD 178 mm, FF | 10 / 16 / 20 | FE2805 |
| DN 65 (2.5") | Ship side / slotted | BSPP (G) / BS336 / NH / Storz / DSP / Machino / Nakajima | OD 178 mm, FF | 10 / 16 / 20 | FE2806 |

Note: For each ISC, it includes accessories 1 fiber gasket, 4 brass hexagon bolts M16 x 50 mm, 4 hexagon nuts, and 8 washers.



ISC cabinet

- Certificate: ISO
- Standard: Refer to FSS code
- Feature: Lightweight, corrosive resistance
- Surface: Red polish

Available size

| Content | Capacity | Material | Mounting | Dimension W x H x D (mm) | Ref. No. |
|--------------------------------|---|------------|----------|--------------------------|----------|
| International shore connection | DN 40 (1.5") / DN 40 (1.5") / DN 65 (2.5"), 1 set | Fiberglass | Surface | 200 x 200 x 190 | FE2811 |
| International shore connection | DN 40 (1.5") / DN 40 (1.5") / DN 65 (2.5"), 1 set | Fiberglass | Surface | 260 x 240 x 210 | FE2812 |
| International shore connection | DN 40 (1.5") / DN 40 (1.5") / DN 65 (2.5"), 1 set | Fiberglass | Surface | 260 x 240 x 235 | FE2813 |