



shore side

ship side



## International shore connection

- Certificate: ISO
- Standard: FSS code
- Material: Brass
- Feature: Connect ship to shore, or ship to ship
- Surface: Rough brass, etc.

### Available size

Size	Type	Thread connection	Flanged connection	Working pressure (bar)	Ref. No.
DN 40 (1.5")	Shore side / non-slotted	BSPP (G) / NH / Storz / DSP / Machino / Nakajima	OD 178 mm, FF	10 / 16 / 20	FE2801
DN 40 (1.5")	Ship side / slotted	BSPP (G) / NH / Storz / DSP / Machino / Nakajima	OD 178 mm, FF	10 / 16 / 20	FE2802
DN 50 (2")	Shore side / non-slotted	BSPP (G) / Storz / Machino / Nakajima	OD 178 mm, FF	10 / 16 / 20	FE2803
DN 50 (2")	Ship side / slotted	BSPP (G) / Storz / Machino / Nakajima	OD 178 mm, FF	10 / 16 / 20	FE2804
DN 65 (2.5")	Shore side / non-slotted	BSPP (G) / BS336 / NH / Storz / DSP / Machino / Nakajima	OD 178 mm, FF	10 / 16 / 20	FE2805
DN 65 (2.5")	Ship side / slotted	BSPP (G) / BS336 / NH / Storz / DSP / Machino / Nakajima	OD 178 mm, FF	10 / 16 / 20	FE2806

**Note:** For each ISC, it includes accessories 1 fiber gasket, 4 brass hexagon bolts M16 x 50 mm, 4 hexagon nuts, and 8 washers.



## ISC cabinet

- Certificate: ISO
- Standard: Refer to FSS code
- Feature: Lightweight, corrosive resistance
- Surface: Red polish

### Available size

Content	Capacity	Material	Mounting	Dimension W x H x D (mm)	Ref. No.
International shore connection	DN 40 (1.5") / DN 40 (1.5") / DN 65 (2.5"), 1 set	Fiberglass	Surface	200 x 200 x 190	FE2811
International shore connection	DN 40 (1.5") / DN 40 (1.5") / DN 65 (2.5"), 1 set	Fiberglass	Surface	260 x 240 x 210	FE2812
International shore connection	DN 40 (1.5") / DN 40 (1.5") / DN 65 (2.5"), 1 set	Fiberglass	Surface	260 x 240 x 235	FE2813