


## Double lugs BS336 adapter with female thread



- Certificate: ISO
- Standard: Refer to BS 336
- Material: Aluminum / brass
- Feature: Instantaneous F to threaded
- Surface: Anodized / rough brass / bright, etc.



### Available size

Size	Material	Instantaneous connection	Threaded connection	Working pressure (bar)	Ref. No.
DN 40 (1.5")	AL / brass	BS336, F	BSP / NH / NPT, F	16	FE5041
DN 50 (2")	AL / brass	BS336, F	BSP / NH / NPT, F	16	FE5042
DN 65 (2.5")	AL / brass	BS336, F	BSP / NH / NPT, F	16	FE5043



## Double lugs BS336 adapter with male thread

- Certificate: ISO
- Standard: Refer to BS 336
- Material: Aluminum / brass
- Feature: Instantaneous F to threaded
- Surface: Anodized / rough brass / bright, etc.



### Available size

Size	Material	Instantaneous connection	Threaded connection	Working pressure (bar)	Ref. No.
DN 40 (1.5")	AL / brass	BS336, F	BSP / NH / NPT, M	16	FE5051
DN 50 (2")	AL / brass	BS336, F	BSP / NH / NPT, M	16	FE5052
DN 65 (2.5")	AL / brass	BS336, F	BSP / NH / NPT, M	16	FE5053