



Inlet stop valve

- Certificate: LPCB Approved/WaterMark
- Standard: BS 5154
- Material: Copper alloy
- Function: For hose reel and hydrant system
- Surface: Rough brass / red coating

Available size

Size	Type	Pressure gauge	Inlet	Outlet	Working pressure (bar)	Ref. No.
DN 25 (1")	Gate valve, handwheel	No	1" BSP, F	1" BSP, F	16 / 20	FE6801(LPCB)
DN 25 (1")	Gate valve, lockshield (Key)	No	1" BSP, F	1" BSP, F	16 / 20	FE6802(LPCB)
DN 25 (1")	Ball valve	No	1" BSP, F	1" BSP, F	16 / 20	FE6803(LPCB)
DN 25 (1")	Ball valve	Yes	1" BSP, F	1" BSP, F	16 / 20	FE6804(LPCB)
DN 25 (1")	Angle valve, handwheel	Yes	1" BSP, F	1" BSP, M	16 / 20	FE6805(LPCB)
DN 25 (1")	Ball valve, lockshield (Key)	No	1" BSP, F	1" BSP, F	18	FE6806(WaterMark)



Pressure reducing valve

- Certificate: ISO
- Standard: Refer to BS EN 671-1
- Material: Copper alloy
- Function: Reduce the inlet pressure of hose reel
- Surface: Chromed brass

Available size

Size	Inlet	Outlet	Max inlet pressure	Outlet pressure regulation	Working pressure (bar)	Ref. No.
DN 25 (1")	1" BSP, F	1" BSP, F	20 bar	1 ~ 4 bar	25	FE6901
DN 40 (1.5")	1.5" BSP, F	1.5" BSP, F	20 bar	1 ~ 4 bar	25	FE6902
DN 50 (2")	2" BSP, F	2" BSP, F	20 bar	1 ~ 4 bar	25	FE6903