


# Spiral wound gasket for EN flange connection



- Certificate: ISO
- Standard: EN 1514-2, GB/T 4622.2, HG/T 20610
- Type: With centering ring (Type C), or with centering ring and inner ring (Type D)
- Thickness: T=4.5mm, T1=3.0mm
- Color: Plain, yellow, green, etc.



Type C



Type D

	Filler			Metal winding, centering ring, inner ring		
<b>Material</b>	Flexible graphite	PTFE	Non asbestos	AISI 304	AISI 316L	Carbon steel
<b>Color</b>	Grey	White	Black	Yellow	Green	Silver
<b>Temperature</b>	-200 ~ 650°C	-200 ~ 200°C	-100 ~ 250°C	/	/	/

## Available size for type C and type D gasket (PN 16 flange)

NPS	Size		Flange type	Gasket size (mm)			Ref. No.
	DN	OD (mm)		D2	D3	D4	
1/2"	15	21.3	PN 16, FF / RF	29	39	53	NE4901-PN16
3/4"	20	26.9	PN 16, FF / RF	34	46	63	NE4902-PN16
1"	25	33.7	PN 16, FF / RF	41	53	73	NE4903-PN16
1-1/4"	32	42.4	PN 16, FF / RF	49	61	84	NE4904-PN16
1-1/2"	40	48.3	PN 16, FF / RF	56	68	94	NE4905-PN16
2"	50	60.3	PN 16, FF / RF	70	86	109	NE4906-PN16
2-1/2"	65	76.1	PN 16, FF / RF	86	102	129	NE4907-PN16
3"	80	88.9	PN 16, FF / RF	99	115	144	NE4908-PN16
4"	100	114.3	PN 16, FF / RF	127	143	164	NE4909-PN16
5"	125	139.7	PN 16, FF / RF	152	172	194	NE4910-PN16
6"	150	165.1 / 168.3	PN 16, FF / RF	179	199	220	NE4911-PN16
8"	200	219.1	PN 16, FF / RF	228	248	275	NE4912-PN16
10"	250	273.0	PN 16, FF / RF	279	303	331	NE4913-PN16
12"	300	323.9	PN 16, FF / RF	334	358	386	NE4914-PN16
14"	350	355.6	PN 16, FF / RF	392	416	446	NE4915-PN16
16"	400	406.4	PN 16, FF / RF	438	466	498	NE4916-PN16
18"	450	457	PN 16, FF / RF	488	516	558	NE4917-PN16
20"	500	508	PN 16, FF / RF	542	570	620	NE4918-PN16
24"	600	610	PN 16, FF / RF	642	670	737	NE4919-PN16

# Spiral wound gasket for EN flange connection

## Available size for type C and type D gasket (PN 25 flange)

Size			Flange type	Gasket size (mm)			Ref. No.
NPS	DN	OD (mm)		D2	D3	D4	
1/2"	15	21.3	PN 25, FF / RF	29	39	53	NE4901-PN25
3/4"	20	26.9	PN 25, FF / RF	34	46	63	NE4902-PN25
1"	25	33.7	PN 25, FF / RF	41	53	73	NE4903-PN25
1-1/4"	32	42.4	PN 25, FF / RF	49	61	84	NE4904-PN25
1-1/2"	40	48.3	PN 25, FF / RF	56	68	94	NE4905-PN25
2"	50	60.3	PN 25, FF / RF	70	86	109	NE4906-PN25
2-1/2"	65	76.1	PN 25, FF / RF	86	102	129	NE4907-PN25
3"	80	88.9	PN 25, FF / RF	99	115	144	NE4908-PN25
4"	100	114.3	PN 25, FF / RF	127	143	170	NE4909-PN25
5"	125	139.7	PN 25, FF / RF	152	172	196	NE4910-PN25
6"	150	165.1 / 168.3	PN 25, FF / RF	179	199	226	NE4911-PN25
8"	200	219.1	PN 25, FF / RF	228	248	286	NE4912-PN25
10"	250	273.0	PN 25, FF / RF	279	303	343	NE4913-PN25
12"	300	323.9	PN 25, FF / RF	334	358	403	NE4914-PN25
14"	350	355.6	PN 25, FF / RF	392	416	460	NE4915-PN25
16"	400	406.4	PN 25, FF / RF	438	466	517	NE4916-PN25
18"	450	457	PN 25, FF / RF	488	516	567	NE4917-PN25
20"	500	508	PN 25, FF / RF	542	570	627	NE4918-PN25
24"	600	610	PN 25, FF / RF	642	670	737	NE4919-PN25