


## Straight type brass globe valve




- Certificate: ISO
- Material: Brass
- Connection: Thread, BSPP (G) / BSPT / NPT
- Temperature: -20°C to 150°C
- W. pressure: PN 16 (1.6 MPa)
- Surface: Rough brass

### Available size

Size		Dimension (mm)			Connection	Working pressure	Ref. No.
Inch	DN	L	H	D			
1/2"	15	46	60	60	BSPP (G) / BSPT / NPT	PN 16	VC1101
3/4"	20	54	68	60	BSPP (G) / BSPT / NPT	PN 16	VC1102
1"	25	67	75	70	BSPP (G) / BSPT / NPT	PN 16	VC1103
1-1/4"	32	77	90	80	BSPP (G) / BSPT / NPT	PN 16	VC1104
1-1/2"	40	83	100	80	BSPP (G) / BSPT / NPT	PN 16	VC1105
2"	50	104	118	105	BSPP (G) / BSPT / NPT	PN 16	VC1106
2-1/2"	65	171	197	179	BSPP (G) / BSPT / NPT	PN 16	VC1107
3"	80	245	277	200	BSPP (G) / BSPT / NPT	PN 16	VC1108
4"	100	271	316	218	BSPP (G) / BSPT / NPT	PN 16	VC1109

## Angle type brass globe valve



- Certificate: ISO
- Material: Brass
- Connection: Thread, NPT
- Temperature: -20°C to 150°C
- W. pressure: 175 psi
- Surface: Rough brass

### Available size

Size		Dimension (mm)			Connection	Working pressure (psi)	Ref. No.
Inch	DN	L	H	D			
1/2"	15	27	84	21.3	NPT	175	VC1201
3/4"	20	32	116	26.7	NPT	175	VC1202
1"	25	40	131	33.4	NPT	175	VC1203
1-1/4"	32	46	142	42.2	NPT	175	VC1204
1-1/2"	40	50	165	48.3	NPT	175	VC1205
2"	50	61	202	60.3	NPT	175	VC1206