


Brass air vent valve (Filtration type)




- Certificate: ISO
- Material: Brass
- Connection: Thread, BSPP (G) / BSPT / NPT
- Temperature: 0°C to 90°C
- W. pressure: PN 16 (1.6 MPa)
- Surface: Rough brass

Available size

Size		Dimension (mm)			Connection	Working pressure	Ref. No.
Inch	DN	H	L	D			
1/2"	15	80	33	37	BSPP (G) / BSPT / NPT	PN 16	VC1701
3/4"	20	80	33	37	BSPP (G) / BSPT / NPT	PN 16	VC1702
1"	25	80	33	37	BSPP (G) / BSPT / NPT	PN 16	VC1703

Brass air admittance valve



- Certificate: ISO
- Material: Brass
- Connection: Thread, BSPP (G) / BSPT / NPT
- Adjustment: Vertically only
- Temperature: 0°C to 90°C
- W. pressure: PN 16 (1.6 MPa)
- Surface: Rough brass

Size		Dimension (mm)		Connection	Working pressure (psi)	Ref. No.
Inch	DN	L	H			
1/2"	15	24	74	BSPP (G) / BSPT / NPT	PN 16	VC1801
3/4"	20	24	76.5	BSPP (G) / BSPT / NPT	PN 16	VC1802
1"	25	28.5	82	BSPP (G) / BSPT / NPT	PN 16	VC1803
1-1/4"	32	34.5	92	BSPP (G) / BSPT / NPT	PN 16	VC1804
1-1/2"	40	42	103	BSPP (G) / BSPT / NPT	PN 16	VC1805
2"	50	52	114.5	BSPP (G) / BSPT / NPT	PN 16	VC1806