


Bronze globe valve




- Certificate: ISO
- Material: Bronze
- Connection: Thread, BSPP (G) / BSPT / NPT
- Temperature: -20°C to 180°C
- W. pressure: PN 20, or PN 25 (Only BSPT)
- Surface: Rough bronze



Available size

Size		Dimension (mm)			Connection	Working pressure	Ref. No.
Inch	DN	L	H	D			
1/2"	15	57	75	60	BSPP (G) / BSPT / NPT	PN 20 / 25	VC3301
3/4"	20	62	83	60	BSPP (G) / BSPT / NPT	PN 20 / 25	VC3302
1"	25	74	84	72	BSPP (G) / BSPT / NPT	PN 20 / 25	VC3303
1-1/4"	32	81	103	72	BSPP (G) / BSPT / NPT	PN 20 / 25	VC3304
1-1/2"	40	89	114	80	BSPP (G) / BSPT / NPT	PN 20 / 25	VC3305
2"	50	108	136	100	BSPP (G) / BSPT / NPT	PN 20 / 25	VC3306
3"	80	158	215	155	BSPP (G) / BSPT / NPT	PN20	VC3307

Bronze swing check valve



- Certificate: ISO
- Material: Bronze
- Connection: Thread, BSPP (G) / BSPT / NPT
- Temperature: -20°C to 180°C
- W. pressure: PN 16, PN 20, or PN 25 (Only BSPT)
- Surface: Rough bronze



Available size

Size		Dimension (mm)		Connection	Working pressure	Ref. No.
Inch	DN	L	H			
1/2"	15	59	37	BSPP (G) / BSPT / NPT	PN 16 / 20 / 25	VC3401
3/4"	20	66	44	BSPP (G) / BSPT / NPT	PN 16 / 20 / 25	VC3402
1"	25	76	50	BSPP (G) / BSPT / NPT	PN 16 / 20 / 25	VC3403
1-1/4"	32	88	58	BSPP (G) / BSPT / NPT	PN 16 / 20 / 25	VC3404
1-1/2"	40	92	63	BSPP (G) / BSPT / NPT	PN 16 / 20 / 25	VC3405
2"	50	112	72	BSPP (G) / BSPT / NPT	PN 16 / 20 / 25	VC3406
3"	80	158	91	BSPP (G) / BSPT / NPT	PN 20	VC3407