


Bronze Y type strainer




- Certificate: ISO
- Material: Bronze
- Connection: Thread, BSPP (G) / BSPT / NPT
- Screen: Standard 18 mesh
- Temperature: -20°C to 180°C
- W. pressure: PN 20, or PN 25 (Only BSPT)
- Surface: Rough bronze



Available size

| Size | | L (mm) | Mesh screen | Connection | Working pressure | Ref. No. |
|--------|----|--------|-------------|-----------------------|------------------|----------|
| Inch | DN | | | | | |
| 1/2" | 15 | 58 | 18 | BSPP (G) / BSPT / NPT | PN 20 / 25 | VC3501 |
| 3/4" | 20 | 70 | 18 | BSPP (G) / BSPT / NPT | PN 20 / 25 | VC3502 |
| 1" | 25 | 82 | 18 | BSPP (G) / BSPT / NPT | PN 20 / 25 | VC3503 |
| 1-1/4" | 32 | 93 | 18 | BSPP (G) / BSPT / NPT | PN 20 / 25 | VC3504 |
| 1-1/2" | 40 | 104 | 18 | BSPP (G) / BSPT / NPT | PN 20 / 25 | VC3505 |
| 2" | 50 | 125 | 18 | BSPP (G) / BSPT / NPT | PN 20 / 25 | VC3506 |
| 3" | 80 | 240 | 18 | BSPP (G) / BSPT / NPT | PN 20 | VC3507 |

3-way bronze globe valve (Gauge valve)



- Certificate: UL Listed
- Material: Bronze
- Connection: Thread, BSPT / NPT
- Temperature: -20°C to 180°C
- W. pressure: 600 / 175 / 300 psi
- Surface: Rough bronze



Available size

| Size | | Dimension (mm) | | | Connection | Working pressure (psi) | Ref. No. |
|------|----|----------------|----|----|------------|------------------------|--------------|
| Inch | DN | L | H | D | | | |
| 1/4" | 8 | 42 | 50 | 54 | BSPT / NPT | 600 | VC3601 (UL) |
| 1/4" | 8 | 44 | 55 | 53 | BSPT / NPT | 175 | VC3602 (UL) |
| 1/4" | 8 | 42 | 64 | 56 | BSPT / NPT | 300 | VC3603 (ISO) |