

Stainless steel screwed NRS gate valve



- Certificate: ISO
- Material: SS304 / SS316
- Connection: Thread, BSPT / BSPP (G) / NPT
- Temperature: -20°C to 180°C
- W. pressure: 200 psi
- Surface: Sandblasted

Available size

Size		Dimension (mm)			Connection	Working pressure (psi)	Ref. No.
Inch	DN	L	H	D			
1/2"	15	45	71	55	BSPT / BSPP (G) / NPT	200	VC6101
3/4"	20	50	76	55	BSPT / BSPP (G) / NPT	200	VC6102
1"	25	55	83	60	BSPT / BSPP (G) / NPT	200	VC6103
1-1/4"	32	60	98	72	BSPT / BSPP (G) / NPT	200	VC6104
1-1/2"	40	63	109	72	BSPT / BSPP (G) / NPT	200	VC6105
2"	50	69	130	80	BSPT / BSPP (G) / NPT	200	VC6106
2-1/2"	65	88	164	100	BSPT / BSPP (G) / NPT	200	VC6107
3"	80	95	180	110	BSPT / BSPP (G) / NPT	200	VC6108
4"	100	114	235	130	BSPT / BSPP (G) / NPT	200	VC6109

Stainless steel screwed globe valve



- Certificate: ISO
- Material: SS304 / SS316
- Connection: Thread, BSPT / BSPP (G) / NPT
- Temperature: -20°C to 180°C
- W. pressure: 200 psi
- Surface: Sandblasted

Available size

Size		Dimension (mm)			Connection	Working pressure (psi)	Ref. No.
Inch	DN	L	H	D			
1/2"	15	46	60	60	BSPT / BSPP (G) / NPT	200	VC6201
3/4"	20	54	68	60	BSPT / BSPP (G) / NPT	200	VC6202
1"	25	67	75	70	BSPT / BSPP (G) / NPT	200	VC6203
1-1/4"	32	77	90	80	BSPT / BSPP (G) / NPT	200	VC6204
1-1/2"	40	83	100	80	BSPT / BSPP (G) / NPT	200	VC6205
2"	50	104	118	105	BSPT / BSPP (G) / NPT	200	VC6206
2-1/2"	65	171	197	179	BSPT / BSPP (G) / NPT	200	VC6207
3"	80	245	277	200	BSPT / BSPP (G) / NPT	200	VC6208
4"	100	271	316	218	BSPT / BSPP (G) / NPT	200	VC6209