

## **Gate valve lockout**



· Certificate: ISO

· Standard: Refer to UL 94-HB

· Material: ABS plastic body, SS bolt

· Temperature: -57°C to 177°C

· Surface: Red ABS

## Available size

| Туре  |                      | Diameter<br>(mm) | Valve type | Valve size    | Padlock     | Ref. No. |
|-------|----------------------|------------------|------------|---------------|-------------|----------|
| Round | d, with padlock hole | 25 ~ 635         | Handwheel  | For 2" to 24" | Yes, or not | V8401    |

Note: Padlock is available to equip together if required.

## Adjustable cable lockout



· Certificate: ISO

Standard: Refer to OSHA 29 CFR 1910.147Material: ABS plastic body, PVC coated cable

· Temperature: -57°C to 177°C

· Surface: Red ABS

## Available size

| Туре                                   | Cable material  | Cable dimension (mm)   | Valve type | Valve size    | Ref. No. |
|--|-----------------|------------------------|------------|---------------|----------|
| Multi-stranded cable with lock and key | Alloy steel     | 4.0 x 1000, adjustable | Handwheel  | For 2" to 24" | V8411    |
| Multi-stranded cable with lock and key | Stainless steel | 3.2 x 1000, adjustable | Handwheel  | For 2" to 24" | V8412    |











