



Pilot operated solenoid valve




- Certificate: UL Listed
- Standard: UL 429
- Material: Brass body, EPDM diaphragm, SS304 spring
- Feature: Normally Closed, pilot operated, 2-way
- Temperature: -10°C to 120°C
- W. pressure: 300 psi
- Surface: Rough brass



Available size

Type	Size	Electrical ratings	Working condition	Working pressure (psi)	Ref. No.
Pilot operated, 2-way	1/2", NPT / BSPT	24VDC / 10W	NC	7.5 ~ 300	V8801
Pilot operated, 2-way	1/2", NPT / BSPT	24VDC / 22W	NC	20 ~ 300	V8802

Direct acting solenoid valve



- Certificate: UL Listed
- Standard: UL 429
- Material: Brass / SS body, NBR or Cast UR seal and disc
- Feature: NC, NO, or univesal, direct acting, 3-way
- Temperature: 0°C to 52°C
- Surface: Brass / SS



Available size

Type	Size	Standard voltage	Working condition	Working pressure (psi)	Ref. No.
Direct acting, 3-way	1/8", NPT	6/12/24/120 VDC	Universal, NC, NO	125, Max DC, water	V8811
Direct acting, 3-way	1/4", NPT	6/12/24/120 VDC	Universal, NC, NO	125, Max DC, water	V8812

Note: For standard voltage, it is also available with 24/120/240/480 VAC 60 Hz, and 110/220 VAC 50Hz.