

Carbon dioxide fire extinguisher

Hand-held portable carbon dioxide (CO₂) fire extinguisher is suitable for fire Class B and C. CO₂ is non conductive and clean, ensuring minimal damage to electrical equipment and furnishings.



- Certificate: UL Listed
- Standard: ANSI / UL 154, ANSI / UL 711
- Fire rating: Class B and C fire
- Marine type: Yes, B.C Size I
- Temperature: -30°C to 49°C
- Surface: Red powder coating

Main parts and material

Cylinder	Aluminum	Extinguishing agent	CO ₂ (Carbon dioxide)
Cylinder valve	Brass, with SS handle	Hose assembly	Rubber, as UL 92

Available size

Capacity (lb)	UL rating	Dimension (inch)		Overall weight (lb)	Discharge time (sec.)	Discharge range (ft)	Ref. No.
		Cylinder dia.	Height				
5	2-B:C	5.2"	17.1"	13.3 Lbs	9	4 ~ 8	F7101
10	10-B:C	6.9"	29.9"	26.7 Lbs	10	4 ~ 8	F7102
15	10-B:C	6.9"	35.8"	36 Lbs	14	4 ~ 8	F7103
20	10-B:C	8"	36"	48 Lbs	18	4 ~ 8	F7104

Note:

1. Wall hook or wall bracket is included for mounting.
2. For F7101 and F7104, they are not Marine type.