


## Grooved straight tee (Equal tee)



- Certificate: UL Listed / FM Approved
- Standard: ANSI / UL 213C
- Material: Ductile iron ASTM A536, 65-45-12
- Type: Short / Standard
- Rated pressure: 300 ~ 500 psi
- Surface: Red painting / hot dip galvanized



### Available size

| Size   |     |       | Center to end, L (mm) |          | Ref. No.      |
|--------|-----|-------|-----------------------|----------|---------------|
| Inch   | DN  | mm    | Short                 | Standard |               |
| 1"     | 25  | 33.7  | 57                    | 57       | G1501 (UL/FM) |
| 1-1/4" | 32  | 42.4  | 60                    | 70       | G1502 (UL/FM) |
| 1-1/2" | 40  | 48.3  | 60                    | 70       | G1503 (UL/FM) |
| 2"     | 50  | 60.3  | 70                    | 83       | G1504 (UL/FM) |
| 2-1/2" | 65  | 73.0  | 76                    | 95       | G1505 (UL/FM) |
| 2-1/2" | 65  | 76.1  | 76                    | 95       | G1506 (UL/FM) |
| 3"     | 80  | 88.9  | 86                    | 108      | G1507 (UL/FM) |
| 4"     | 100 | 114.3 | 101                   | 127      | G1508 (UL/FM) |
| 5"     | 125 | 139.7 | 124                   | 140      | G1509 (UL/FM) |
| 5"     | 125 | 141.3 | 124                   | 140      | G1510 (UL/FM) |
| 6"     | 150 | 165.1 | 140                   | 165      | G1511 (UL/FM) |
| 6"     | 150 | 168.3 | 140                   | 165      | G1512 (UL/FM) |
| 8"     | 200 | 219.1 | 175                   | 197      | G1513 (UL/FM) |
| 10"    | 250 | 273.0 | 215                   | 229      | G1514 (UL/FM) |
| 12"    | 300 | 323.9 | 245                   | 254      | G1515 (UL/FM) |

## Grooved straight tee (Equal tee)

### Available size

| Size |     |       | Center to end, L (mm) |      | Ref. No.   |
|------|-----|-------|-----------------------|------|------------|
| Inch | DN  | mm    | Standard              | Long |            |
| 14"  | 350 | 355.6 | /                     | 280  | G1516 (UL) |
| 16"  | 400 | 406.4 | /                     | 305  | G1517 (UL) |
| 18"  | 450 | 457.2 | /                     | 342  | G1518 (UL) |
| 20"  | 500 | 508   | /                     | 381  | G1519 (UL) |
| 24"  | 600 | 609.6 | /                     | 432  | G1520 (UL) |