


Grooved reducing cross



- Certificate: UL Listed / FM Approved
- Standard: ANSI / UL 213C
- Material: Ductile iron ASTM A536, 65-45-12
- Rated pressure: 300 ~ 500 psi
- Surface: Red painting / hot dip galvanized



Available size

Size			Center to end (mm)		Ref. No.
Inch	DN	mm	L1	L2	
2-1/2" x 2"	65 x 50	76.1 x 60.3	76	76	G2601 (UL/FM)
3" x 2"	80 x 50	88.9 x 60.3	86	86	G2602 (UL/FM)
4" x 2"	100 x 50	114.3 x 60.3	101	101	G2603 (UL/FM)
4" x 3"	100 x 80	114.3 x 88.9	101	101	G2604 (UL/FM)
5" x 4"	125 x 100	139.7 x 114.3	124	124	G2605 (UL/FM)
6" x 2"	150 x 50	165.1 x 60.3	140	140	G2606 (UL/FM)
6" x 2-1/2"	150 x 65	165.1 x 76.1	140	140	G2607 (UL/FM)
6" x 3"	150 x 80	165.1 x 88.9	140	140	G2608 (UL/FM)
6" x 4"	150 x 100	165.1 x 114.3	140	140	G2609 (UL/FM)
6" x 2"	150 x 50	168.3 x 60.3	140	140	G2610 (UL)
8" x 2"	200 x 50	219.1 x 60.3	175	175	G2611 (UL/FM)
8" x 4"	200 x 100	219.1 x 114.3	175	175	G2612 (UL/FM)
8" x 5"	200 x 125	219.1 x 139.7	175	175	G2613 (UL/FM)
8" x 6"	200 x 150	219.1 x 165.1	175	175	G2614 (UL/FM)