


Grooved reducing cross with female threaded branch



- Certificate: UL Listed / FM Approved
- Standard: ANSI / UL 213C
- Material: Ductile iron ASTM A536, 65-45-12
- Branch: Female thread, NPT / BSPT
- Rated pressure: 300 ~ 500 psi
- Surface: Red painting / hot dip galvanized



Available size

Size			Center to end (mm)		Ref. No.
Inch	DN	mm	L1	L2	
2-1/2" x 2"	65 x 50	76.1 x 60.3	76	76	G2701 (UL/FM)
3" x 1-1/4"	80 x 32	88.9 x 42.4	86	86	G2702 (UL)
3" x 1-1/2"	80 x 40	88.9 x 48.3	86	86	G2703 (UL/FM)
3" x 2"	80 x 50	88.9 x 60.3	86	86	G2704 (UL/FM)
4" x 1"	100 x 25	114.3 x 33.7	101	101	G2705 (UL/FM)
4" x 1-1/4"	100 x 32	114.3 x 42.4	101	101	G2706 (UL/FM)
4" x 1-1/2"	100 x 40	114.3 x 48.3	101	101	G2707 (UL/FM)
4" x 2"	100 x 50	114.3 x 60.3	101	101	G2708 (UL/FM)
4" x 2-1/2"	100 x 65	114.3 x 76.1	101	101	G2709 (UL/FM)
4" x 3"	100 x 80	114.3 x 88.9	101	101	G2710 (UL/FM)
6" x 1-1/4"	150 x 32	165.1 x 42.4	140	140	G2711 (ISO)
6" x 1-1/2"	150 x 40	165.1 x 48.3	140	140	G2712 (UL/FM)
6" x 2"	150 x 50	165.1 x 60.3	140	140	G2713 (UL/FM)
6" x 2-1/2"	150 x 65	165.1 x 76.1	140	140	G2714 (ISO)
6" x 3"	150 x 80	165.1 x 88.9	140	140	G2715 (ISO)