



## Storz outlet oblique type landing valve

- Certificate: ISO
- Standard: DIN 14461-3
- Material: Copper alloy / aluminum
- Feature: Oblique type, Storz outlet
- Surface: Rough / polish / red coating

### Available size

Size	Type	Inlet	Outlet	Working pressure (bar)	Ref. No.
DN 40 (1.5")	Oblique	BSPP (G) 1.5", M or F	Storz C 38, 1.5"	16	FE1701
DN 50 (2")	Oblique	BSPP (G) 2", M or F	Storz C 52, 2"	16	FE1702
DN 65 (2.5")	Oblique	BSPP (G) 2.5", M or F	Storz B 65, 2.5"	16	FE1703
DN 80 (3")	Oblique	BSPP (G) 3", M or F	Storz B 65, 2.5"	16	FE1704



## Storz outlet angle type landing valve

- Certificate: ISO
- Standard: DIN 14461-3
- Material: Copper alloy / aluminum
- Feature: Angle type, Storz outlet
- Surface: Rough / polish / red coating

### Available size

Size	Type	Inlet	Outlet	Working pressure (bar)	Ref. No.
DN 40 (1.5")	Angle	BSPP (G) 1.5", M or F	Storz C 38, 1.5"	16	FE1711
DN 50 (2")	Angle	BSPP (G) 2", M or F	Storz C 52, 2"	16	FE1712
DN 65 (2.5")	Angle	BSPP (G) 2.5", M or F	Storz B 65, 2.5"	16	FE1713
DN 80 (3")	Angle	BSPP (G) 3", M or F	Storz B 65, 2.5"	16	FE1714