

Dry powder fire extinguisher

Fire extinguisher contains extinguishing medium which is expelled by the action of internal pressure and directed to combat a fire. For portable dry powder fire extinguisher, it is multi-purpose for against Class A, B, and C fire.



- Certificate: BSI / LPCB / CE Approved
- Standard: BS EN 3-7 / 3-8 / 3-10
- Fire rating: Class A, B and C fire
- Temperature: -30°C to 60°C
- W. pressure: 15 bar
- Test: 27 bar
- Surface: Red powder coating

Main parts and material

Cylinder	Deep drawn steel, DC01 or DC04 to EN 10130	Extinguishing medium	ABC powder 40% MAP, as EN 615
Control valve	Brass, with pressure indicator	Hose assembly	Rubber, with hose retaining clip

Available size

Capacity (kg)	BSI / LPCB rating	Dimension (mm)		Overall weight (kg)	Discharge time (sec.)	Discharge range (m)	Ref. No.
		Cylinder dia.	Height				
1	8A & 34B	85	315	1.9	6.5	3 ~ 5	FE8001
2	13A & 89B	110	383	3.6	13.5	3 ~ 5	FE8002
3	21A & 113B	130	483	5.2	15	3 ~ 5	FE8003
4	27A & 144B	130	490	6.8	17	3 ~ 5	FE8004
6	43A & 233B	154	540	9.3	17	3 ~ 5	FE8005
9	55A & 233B	182	556	13.7	19	3 ~ 5	FE8006
12	55A & 233B	190	672	17.4	30	3 ~ 5	FE8007

Note: Fire extinguisher bracket is included.