

Foam fire extinguisher

Fire extinguisher contains extinguishing medium which is expelled by the action of internal pressure and directed to combat a fire. For portable foam fire extinguisher, it is suitable for against Class A and B fire.



- Certificate: BSI / LPCB / CE Approved
- Standard: BS EN 3-7 / 3-8 / 3-10
- Fire rating: Class A and B fire
- Temperature: 5°C to 60°C
- W. pressure: 15 bar
- Test: 27 bar
- Surface: Red powder coating



Main parts and material

Cylinder	Deep drawn steel, DC01 or DC04 to EN 10130	Extinguishing medium	AFFF foam
Control valve	Brass, with pressure indicator	Hose assembly	Rubber, with hose retaining clip

Available size

Capacity (L)	BSI / LPCB rating	Dimension (mm)		Overall weight (kg)	Discharge time (sec.)	Discharge range (m)	Ref. No.
		Cylinder dia.	Height				
2	8A & 55B	110	403	3.6	15	3 ~ 5	FE8201
3	13A & 89B	130	438	5.2	20	3 ~ 5	FE8202
6	21A & 144B	162	537	9.6	22	3 ~ 5	FE8203
9	27A & 233B	182	620	14	30	3 ~ 5	FE8204

Note: Fire extinguisher bracket is included.