

Mobile fire extinguisher

Mobile fire extinguisher is mounted on wheels for easy movement. Comparing portable extinguisher, it features bigger extinguishing medium capacity for larger fire protection area, manoeuvred by an operator on foot only.



- Certificate: LPCB / CE Approved
- Standard: BS EN 1866-1
- Fire rating: Class A, B and C fire
- Temperature: -30°C to 60°C (5°C to 60°C for foam)
- W. pressure: 15 bar (150 bar for CO₂)
- Test: 27 bar (225 bar for CO₂)
- Surface: Red powder coating



Main parts and material

Cart, framing and cylinder	Rugged steel	Extinguishing medium	ABC powder, AFFF foam, or Carbon dioxide
Control valve	Brass, with pressure indicator (Not for CO ₂ type)	Hose assembly	Rubber, with hose valve (Not for CO ₂ type)

Available size

Type	Capacity	BSI / LPCB rating	Dimension (mm)		Overall weight (kg)	Discharge time (sec.)	Discharge range (m)	Ref. No.
			Cylinder dia.	Height				
ABC powder	25 kg	II B	250	870	40	30	4 ~ 6	FE8501
ABC powder	50 kg	IV B	300	1200	77	35	4 ~ 6	FE8502
ABC powder	100 kg	IV B	400	1200	140	35	4 ~ 6	FE8503
CO ₂	10 kg	144 B	152	1220	46	35	4 ~ 6	FE8504
CO ₂	20 kg	183 B	219	1305	100	35	4 ~ 6	FE8505
CO ₂	30 kg	183 B	219	1590	117	35	4 ~ 6	FE8506
Foam	50 L	IV B	300	1200	77	35	4 ~ 6	FE8507
Foam	100 L	IV B	400	1200	140	35	4 ~ 6	FE8508