


Grooved reducing tee with female threaded branch



- Certificate: UL Listed / FM Approved
- Standard: ANSI / UL 213C
- Material: Ductile iron ASTM A536, 65-45-12
- Type: Short / Standard
- Branch: Female thread, NPT / BSPT
- Rated pressure: 300 ~ 500 psi
- Surface: Red painting / hot dip galvanized



Available size

Size			Center to end (mm), Short		Center to end (mm), Standard		Ref. No.
Inch	DN	mm	L1	L2	L1	L2	
1-1/4" x 1"	32 x 25	42.4 x 33.7	60	60	/	/	G2101 (UL)
1-1/2" x 1"	40 x 25	48.3 x 33.7	60	60	/	/	G2102 (UL)
1-1/2" x 1-1/4"	40 x 32	48.3 x 42.4	60	60	/	/	G2103 (UL)
2" x 1"	50 x 25	60.3 x 33.7	70	70	83	83	G2104 (UL/FM)
2" x 1-1/4"	50 x 32	60.3 x 42.4	70	70	/	/	G2105 (UL/FM)
2" x 1-1/2"	50 x 40	60.3 x 48.3	70	70	/	/	G2106 (UL/FM)
2-1/2" x 1"	65 x 25	73.0 x 33.7	76	76	/	/	G2107 (UL/FM)
2-1/2" x 1-1/4"	65 x 32	73.0 x 42.4	76	76	95	95	G2108 (UL/FM)
2-1/2" x 1-1/2"	65 x 40	73.0 x 48.3	76	76	95	95	G2109 (UL/FM)
2-1/2" x 2"	65 x 50	73.0 x 60.3	76	76	/	/	G2110 (UL/FM)
2-1/2" x 1"	65 x 25	76.1 x 33.7	76	76	/	/	G2111 (UL/FM)
2-1/2" x 1-1/4"	65 x 32	76.1 x 42.4	76	76	/	/	G2112 (UL/FM)
2-1/2" x 1-1/2"	65 x 40	76.1 x 48.3	76	76	/	/	G2113 (UL/FM)
2-1/2" x 2"	65 x 50	76.1 x 60.3	76	76	/	/	G2114 (UL/FM)
3" x 1"	80 x 25	88.9 x 33.7	86	86	108	108	G2115 (UL/FM)

Grooved reducing tee with female threaded branch

Available size

Size			Center to end (mm), Short		Center to end (mm), Standard		Ref. No.
Inch	DN	mm	L1	L2	L1	L2	
3" x 1-1/4"	80 x 32	88.9 x 42.4	86	86	108	108	G2116 (UL/FM)
3" x 1-1/2"	80 x 40	88.9 x 48.3	86	86	/	/	G2117 (UL/FM)
3" x 2"	80 x 50	88.9 x 60.3	86	86	/	/	G2118 (UL/FM)
3" x 2-1/2"	80 x 65	88.9 x 76.1	86	86	/	/	G2119 (UL/FM)
4" x 1"	100 x 25	114.3 x 33.7	101	101	127	127	G2120 (UL/FM)
4" x 1-1/4"	100 x 32	114.3 x 42.4	101	101	/	/	G2121 (UL/FM)
4" x 1-1/2"	100 x 40	114.3 x 48.3	101	101	127	127	G2122 (UL/FM)
4" x 2"	100 x 50	114.3 x 60.3	101	101	127	127	G2123 (UL/FM)
4" x 2-1/2"	100 x 65	114.3 x 76.1	101	101	/	/	G2124 (UL/FM)
4" x 3"	100 x 80	114.3 x 88.9	101	101	127	127	G2125 (UL/FM)
5" x 1"	125 x 25	139.7 x 33.7	124	124	/	/	G2126 (UL/FM)
5" x 1-1/4"	125 x 32	139.7 x 42.4	124	124	/	/	G2127 (UL/FM)
5" x 1-1/2"	125 x 40	139.7 x 48.3	124	124	/	/	G2128 (UL/FM)
5" x 2"	125 x 50	139.7 x 60.3	124	124	/	/	G2129 (UL/FM)
5" x 2-1/2"	125 x 65	139.7 x 76.1	124	124	/	/	G2130 (UL/FM)
5" x 3"	125 x 80	139.7 x 88.9	124	124	/	/	G2131 (UL/FM)
6" x 1"	150 x 25	165.1 x 33.7	140	140	/	/	G2132 (UL/FM)
6" x 1-1/4"	150 x 32	165.1 x 42.4	140	140	/	/	G2133 (UL/FM)
6" x 1-1/2"	150 x 40	165.1 x 48.3	140	140	/	/	G2134 (UL/FM)
6" x 2"	150 x 50	165.1 x 60.3	140	140	/	/	G2135 (UL/FM)
6" x 2-1/2"	150 x 65	165.1 x 76.1	140	140	/	/	G2136 (UL/FM)
6" x 3"	150 x 80	165.1 x 88.9	140	140	/	/	G2137 (UL/FM)
6" x 1-1/4"	150 x 32	168.3 x 42.4	140	140	/	/	G2138 (UL/FM)
6" x 1-1/2"	150 x 40	168.3 x 48.3	140	140	/	/	G2139 (UL/FM)
6" x 2"	150 x 50	168.3 x 60.3	140	140	165	165	G2140 (UL/FM)
6" x 2-1/2"	150 x 65	168.3 x 76.1	140	140	/	/	G2141 (UL/FM)
6" x 3"	150 x 80	168.3 x 88.9	140	140	165	165	G2142 (UL/FM)