


Flanged eccentric reducer

Flanged eccentric reducer is designed to connect outlet of fire pump and inlet of subsequent pipeline, so reduce the friction loss by reducing velocity of medium in the pipeline. It can be installed top-flat or bottom-flat.



- Certificate: ISO
- Standard: Refer to NFPA 20
- Connection: Flanged as ANSI B16.5 Class 150 / 300, EN 1092-1 PN16 / PN25, etc.
- Material: Carbon steel / SS304
- W. pressure: 300 psi
- Surface: Red / blue painting



Available size

Size		L (mm)	Connection	Working pressure (psi)	Ref. No.
Inch	DN				
2" x 2-1/2"	50 x 65	110	Class 150 / PN16	300	U3401
2" x 3"	50 x 80	110	Class 150 / PN16	300	U3402
2" x 4"	50 x 100	120	Class 150 / PN16	300	U3403
2" x 5"	50 x 125	145	Class 150 / PN16	300	U3404
2" x 6"	50 x 100	160	Class 150 / PN16	300	U3405
2" x 8"	50 x 200	170	Class 150 / PN16	300	U3406
2-1/2" x 3"	65 x 80	110	Class 150 / PN16	300	U3407
2-1/2" x 4"	65 x 100	120	Class 150 / PN16	300	U3408
2-1/2" x 5"	65 x 125	145	Class 150 / PN16	300	U3409
2-1/2" x 6"	65 x 150	160	Class 150 / PN16	300	U3410
2-1/2" x 8"	65 x 200	170	Class 150 / PN16	300	U3411
3" x 4"	80 x 100	120	Class 150 / PN16	300	U3412
3" x 5"	80 x 125	145	Class 150 / PN16	300	U3413
3" x 6"	80 x 150	160	Class 150 / PN16	300	U3414
3" x 8"	80 x 200	170	Class 150 / PN16	300	U3415
3" x 10"	80 x 250	200	Class 150 / PN16	300	U3416
4" x 5"	100 x 125	145	Class 150 / PN16	300	U3417
4" x 6"	100 x 150	160	Class 150 / PN16	300	U3418
4" x 8"	100 x 200	170	Class 150 / PN16	300	U3419
4" x 10"	100 x 250	200	Class 150 / PN16	300	U3420
5" x 6"	125 x 150	160	Class 150 / PN16	300	U3421
5" x 8"	125 x 200	170	Class 150 / PN16	300	U3422

Flanged eccentric reducer

Available size

Size		L (mm)	Connection	Working pressure (psi)	Ref. No.
Inch	DN				
5" x 10"	125 x 250	200	Class 150 / PN16	300	U3423
6" x 8"	150 x 200	170	Class 150 / PN16	300	U3424
6" x 10"	150 x 250	200	Class 150 / PN16	300	U3425
6" x 12"	150 x 300	220	Class 150 / PN16	300	U3426
8" x 10"	200 x 250	200	Class 150 / PN16	300	U3427
8" x 12"	200 x 300	220	Class 150 / PN16	300	U3428
10" x 12"	250 x 300	220	Class 150 / PN16	300	U3429

Note: For flanged connection, it is available with ANSI B16.5 Class 150 / 300, EN 1092-2 PN10 / PN16 / PN25, etc.