

Vacuum pressure gauge



- Certificate: ISO
- Standard: BS EN 837-1
- Material: SS case, aluminum dial
- Connection: Thread, NPT / BSPT
- Function: Pump suction piping pressure
- Temperature: -40°C to 70°C
- Surface: Bright SS

Available size

Connection size		Dial size (mm)	Scale value (psi)	Accuracy	Working pressure (psi)	Ref. No.
Inch	DN					
1/4"	8	100	-14.5 ~ 300	2.5% ~ 1.6% ~ 1.0%	300	V9601
1/2"	15	100	-14.5 ~ 300	2.5% ~ 1.6% ~ 1.0%	300	V9602

Pressure gauge buffer tube (Syphon)



- Certificate: ISO
- Material: SS304 / SS316L
- Connection: Thread, BSPT / NPT
- Function: Buffer the impact of medium to gauge
- Size: Length 245mm, circle ID 95mm
- Temperature: Up to 400°C
- Surface: Bright SS

Available size

Male thread to valve	Female thread to gauge	Connection	Direction	Working pressure	Ref. No.
1/4", DN8	1/4" or 1/2"	NPT/ BSPT	Straight / angle	PN 40	V9701
3/8", DN10	1/4" or 1/2"	NPT/ BSPT	Straight / angle	PN 40	V9702
1/2", DN15	1/4" or 1/2"	NPT/ BSPT	Straight / angle	PN 40	V9703
3/4", DN20	1/4" or 1/2"	NPT/ BSPT	Straight / angle	PN 40	V9704
1", DN25	1/4" or 1/2"	NPT/ BSPT	Straight / angle	PN 40	V9705

V96-97/